

029-040



Safety data sheet

according to 1907/2006/EC, Article 31

PIN 1824

Page 1/9

Printing date 01-11-2018

Revision: 01-11-2018

Version number 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Trade name: 01 001824 AUTOSOL® Aluminium Polish (75ml Tube)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Application of the substance / the mixture Maintenance product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Autosol, LLC
P.O. Box 340358
Austin, TX 78734

Tel.: 1-512-804-9337

www.autosol.com

Further information obtainable from:

msds@autosol.com

1.4 Emergency telephone number:

1-512-804-9337 or 1-800-314-5545 Toll Free US and Canada

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant


R38: Irritating to skin.

R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Page 2/9

Printing date 01-11-2018
Revision: 01-11-2018

Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

(Contd. of page 1)

• **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

• **Hazard pictograms**



GHS07

• **Signal word Warning**

• **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

• **Precautionary statements**

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection / face protection.

P273 Avoid release to the environment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Additional information:** Keep out of reach of children.

• **2.3 Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

• **3.2 Chemical characterisation: Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Xn R65; F R11; N R51/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; STOT SE 3, H336	10-25%
--------------------------------------	---	--------

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Page 3/9
Printing date 01-11-2018
Revision: 01-11-2018
Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

		(Contd. of page 2)
CAS: 8008-20-6 EINECS: 232-366-4	Kerosine (petroleum) ☒ Xn R65 ⊠ Asp. Tox. 1, H304; Aquatic Chronic 3, H412	10-25%
CAS: 100-37-8 EINECS: 202-845-2	2-diethylaminoethanol ☒ C R34; ☒ Xn R20/21/22 R10 ⊠ Flam. Liq. 3, H226; ⊠ Acute Tox. 3, H311; Acute Tox. 3, H331; ⊠ Skin Corr. 1B, H314; ⊠ Acute Tox. 4, H302; STOT SE 3, H335	1-10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol ☒ F R11 ⊠ Flam. Liq. 2, H225	1-10%

• **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

(Contd. on page 4)



Safety data sheet
according to 1907/2006/EC, Article 31

Page 4/9
Printing date 01-11-2018
Revision: 01-11-2018
Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

(Contd. of page 3)

- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

· **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Filter A/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Page 5/9
Printing date 01-11-2018
Revision: 01-11-2018
Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

Recommended thickness of the material: ≥ 0.5 mm

Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Goggles recommended during refilling

SECTION 9: Physical and chemical properties

• **9.1 Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:	Pasty
Colour:	Grey
• Odour:	Characteristic
• Odour threshold:	Not determined.

• **pH-value:** Not determined.

• **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C

• **Flash point:** > 100 °C

• **Flammability (solid, gaseous):** Not applicable.

• **Ignition temperature:**

Decomposition temperature: Not determined.

• **Self-igniting:** Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

• **Explosion limits:**


Lower:	Not determined.
Upper:	Not determined.

• **Vapour pressure:** Not determined.

• **Density at 20 °C:** 1.048 g/cm³

• **Relative density:** Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Page 6/9
Printing date 01-11-2018
Revision: 01-11-2018
Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

(Contd. of page 5)

· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:

· LD/LC50 values relevant for classification:		
64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	2800 mg/kg (rabbit)
Inhalative	LC50 (4 h)	>23.3 mg/l (rat)
8008-20-6 Kerosine (petroleum)		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rabbit)
100-37-8 2-diethylaminoethanol		
Oral	LD50	1300 mg/kg (rat)
Inhalative	LC50 (4 h)	5 mg/l (mouse)
64-17-5 ethanol		
Oral	LD50	10470 mg/kg (rat) (OECD 401 (Acute Oral Toxicity))
Dermal	LD50	>2000 mg/kg (rabbit) (OECD 402 (Acute Dermal Toxicity))
Inhalative	LC50 (4 h)	117-125 mg/l (rat) (OECD 403 (Acute Inhalation Toxicity))

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Page 7/9
Printing date 01-11-2018
Revision: 01-11-2018
Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

(Contd. of page 6)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64-17-5 ethanol

LC50 (48 h) 12340 mg/l (daphnia)

LC50 (96 h) 13000 mg/l (fish)

· 12.2 Persistence and degradability

64-17-5 ethanol

BCF 3.2 mg/l (Bioconcentrationfactor)

log POW -0.32 (log POW)

· 12.3 Bioaccumulative potential

 No further relevant information available.

· 12.4 Mobility in soil

 No further relevant information available.

· Ecotoxicological effects:

· Remark:

 Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· PBT:

 Not applicable.

· vPvB:

 Not applicable.

· 12.6 Other adverse effects

 No further relevant information available.


SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Page 8/9
Printing date 01-11-2018
Revision: 01-11-2018
Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	-

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.


SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 9)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Page 9/9
Printing date 01-11-2018
Revision: 01-11-2018
Version number 1

Trade name: 01 001824 AUTOSOL® Aluminium Polish

(Contd. of page 8)

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
R10 Flammable.
R11 Highly flammable.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R34 Causes burns.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.

• **Department issuing MSDS:**

AUTOSOL
P.O. Box 340358
Austin, TX 78734

• **Contact:** msds@autosol.com

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Acute Tox. 3: Acute toxicity, Hazard Category 3
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3
