110-016



Revision Date 18-Apr-2016

Version 3

SAFETY DATA SHEET

1. IDENTIFICATION

Product identifier

Product Name

14H THREAD SEALANT W/PTFE 4 FL.OZ.

Other means of identification

Product Code

80632 None

Synonyms

Recommended use of the chemical and restrictions on use Recommended Use

Sealant

Uses advised against

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Distributor

ITW Permatex 6875 Parkland Blvd.

ITW Permatex Canada 35 Brownridge Road, Unit 1

Solon, OH 44139 USA

Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number

1-87-Permatex (877) 376-2839

24 Hour Emergency Phone Number

Chem-Tel: 800-255-3924

International Emergency: 00+1+813-248-0585

Contract Number: MIS0003453

E-mail address

mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	
Carcinogenicity	Category 4
Specific target organ toxicity (single exposure)	Category 2
Flammable liquids	Category 1
- Induito	Category 3

Label elements

Emergency Overview

Danger

Harmful if swallowed May cause cancer Causes damage to organs Flammable liquid and vapor



Appearance White

Physical state Paste

Odor Alcoholic

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

In case of fire: Use Water spray, fog or regular foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

65.99515 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name ETHANOL	CAS No	Weight-%	Trade Secret
	64-17-5	10 - 30	*
2-PROPANOL	67-63-0	1-5	
METHANOL	67-56-1	1-5	
METHYL ISOBUTYL KETONE *The exact percentage (concer	108-10-1	01.4	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash with soap and water. If symptoms persist, call a physician.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms

See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Remove all sources of ignition. Use personal protective equipment as required. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing.

Wash thoroughly after handling.

Environmental precautions

Environmental precautions

Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store locked up.

Incompatible materials

Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m³ (vacated) TWA: 1000 ppm	NIOSH IDLH IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
2-PROPANOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	(vacated) TWA: 1900 mg/m³ TWA: 400 ppm TWA: 980 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
METHANOL 67-56-1 THYL ISOBUTYL KETONE	STEL: 250 ppm TWA: 200 ppm S*	(vacated) STEL: 1225 mg/m³ TWA: 200 ppm TWA: 260 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m³ (vacated) STEL: 325 mg/m³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
108-10-1 HIDLH Immediately Dangerou	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m³ STEL: 75 ppm STEL: 300 mg/m³

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

Remarks • Method

Tag Closed Cup

Butyl acetate = 1

Air = 1

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state **Appearance**

Odor Odor threshold **Paste** White

No information available

Property

На Melting point / freezing point Boiling point / boiling range

Flash point **Evaporation rate**

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit: Lower flammability limit:

Vapor pressure Vapor density Relative density

Water solubility Solubility in other solvents Partition coefficient Autoignition temperature

Decomposition temperature Kinematic viscosity Dynamic viscosity **Explosive properties** Oxidizing properties

Other Information Softening point Molecular weight VOC Content (%)

Density **Bulk density** Alcoholic

<u>Values</u>

No information available No information available 82 °C / 180 °F

25 °C / 77 °F < 1

No information available

12.7% 2.3%

33 mm Hg @ 68°F

1.06-1.10 Partially soluble No information available

No information available No information available No information available No information available No information available No information available No information available

No information available No information available

29.5%%

No information available No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides **Fluorides**

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis.

Ingestion

Harmful if swallowed.

Chemical Name ETHANOL	Oral LD50	Dermal LD50	Inhalation LC50
64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m³ (Rat) 4 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 6400
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	ppm (Rat)4 h = 8.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available. No information available.

Germ cell mutagenicity Carcinogenicity

Chemical Name THANOL	ACGIH	low indicates whether each	NTP	
64-17-5	A3	Group 1	Known	OSHA X
METHYL ISOBUTYL ETONE	A3	Group 2B		×
08-10-1 ACGIH (American Confer				,

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

Chronic toxicity

May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects

Blood, Central nervous system, Central Vascular System (CVS), Eyes, Gastrointestinal

tract (GI), Liver, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)

1811 mg/kg

ATEmix (dermal) ATEmix (inhalation-dust/mist)

6521 mg/kg 11.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

35.44605 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants		<u>ient</u>
ETHANOL	ragaciadatic plants	Fish	Crustacea
64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h	9268 - 14221: 48 h Daphnia mag mg/L LC50 2: 48 h Daphnia mag
		Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h	mg/L EC50 Static 10800: 24 h
		Pimephales promelas mg/L LC50	Daphnia magna mg/L EC50
2-PROPANOL	1000: 96 h Desmodesmus	flow-through	
67-63-0	subspicatus mg/L EC50 1000: 72 h	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96	13299: 48 h Daphnia magna mg
	Desmodesmus subspicatus mg/L	h Pimephales promelas mg/L LC50	EC50
	EC50	static 1400000: 96 h Lepomis	
METHANOL		macrochirus µg/L LC50	
67-56-1		28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h	•
		Pimephales promelas mg/L LC50	
		static 19500 - 20700: 96 h	
•		Oncorhynchus mykiss ma/L LC50	
		flow-through 13500 - 17600: 96 h	
		Lepomis macrochirus mg/L LC50	
		flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50	
THYL ISOBUTYL KETONE	400	static	
108-10-1	400: 96 h Pseudokirchneriella	496 - 514: 96 h Pimephales	170: 48 h Daphnia magna mg/L
	subcapitata mg/L EC50	promelas mg/L LC50 flow-through	EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition acasti at a s
ETHANOL	Partition coefficient
64-17-5	-0.32
2-PROPANOL	0.05
67-63-0	0.05
METHANOL	0.77
67-56-1	-0.77
METHYL ISOBUTYL KETONE	
108-10-1	1.19

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001

Chemical Name				
METHANOL	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHANUL		Included in waste stream:	-	U154
	-		·	U 154

67-56-1 METHYL ISOBUTYL KETONE 108-10-1	F039 Included in waste stream: F039	U161

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	
ETHANOL	California Hazardous Waste Status
64-17-5	Toxic
2-PROPANOL	Ignitable
67-63-0	Toxic
METHANOL	Ignitable
67-56-1	Toxic
	lgnitable

14. TRANSPORT INFORMATION

DOT

UN/ID no

1133

Proper shipping name:

Adhesives, Limited Quantity (LQ)

Hazard Class

Packing Group

Ш

Emergency Response Guide

128

Number

IATA

UN/ID no

ID 8000

Proper shipping name:

Consumer commodity

Hazard Class

9L

ERG Code

IMDG

1133

Proper shipping name:

Adhesives, Limited Quantity (LQ)

Hazard Class

Packing Group

Ш

EmS-No

UN/ID no

F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Not Listed. **ENCS** Not Listed. **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	
2-PROPANOL - 67-63-0	SARA 313 - Threshold Values %
METHANOL - 67-56-1	1.0
SARA 311/312 Hazard Categories	1.0
Acute health hazard Chronic Health Hazard	Yes

Chronic Health Hazard No Fire hazard Yes Sudden release of pressure hazard No **Reactive Hazard** No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	U		
METHANOL	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
67-56-1	5000 lb	-	RQ 5000 lb final RQ
METHYL ISOBUTYL KETONE	5000 lb		RQ 2270 kg final RQ
108-10-1	0000 15	-	RQ 5000 lb final RQ
US State Regulations			RQ 2270 kg final RQ

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	
ETHANOL - 64-17-5	California Proposition 65
	Carcinogen
TITANIUM DIOXIDE - 13463-67-7	Developmental
METHANOL - 67-56-1	Carcinogen
METHYL ISOBUTYL KETONE - 108-10-1	Developmental
	Carcinogen
U.S. State Right-to-Know Regulations	Developmental Developmental
- Tages to the Negulations	

Chemical Name	New Jersey	Massachusetts	
TALC 14807-96-6	X	X	Pennsylvania
ETHANOL			^
64-17-5	X	X	X
2-PROPANOL 67-63-0	X	X	
TITANIUM DIOXIDE	X		
13463-67-7		X	X
WATER 7732-18-5	-	-	Х
METHANOL 67-56-1	X	X	Х
OLYTETRAFLUOROETHYLENE 9002-84-0	•	<u>-</u>	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	×

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA HMIS

Health hazards 2 Health hazards 2

Flammability 3 Flammability 3

Instability 0

Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

18-Apr-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet