



SAFETY DATA SHEET

Revision Date 16-May-2018

Version 4

1. IDENTIFICATION

Product identifier

Product Name

PERMA SHIELD GASKET DRESSING & FLANGE SEALANT 2 FL.OZ

Other means of identification

Product Code

85420

Recommended use of the chemical and restrictions on use

Recommended Use

Sealant.

Uses advised against

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

May Also Be Distributed by:

ITW Permatex

ITW Permatex Canada 101-2360 Bristol Circle

6875 Parkland Blvd. Solon, OH 44139 USA

Oakville, ON Canada L6H 6M5

Telephone: (800) 924-6994

24-hour emergency phone number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address

mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

Label elements

Emergency Overview

Signal word

Danger

Causes serious eye irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Highly flammable liquid and vapor



Appearance Blue

Physical state Liquid

Odor Ketone

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling In case of inadequate ventilation wear respiratory protection Contaminated work clothing should not be allowed out of the workplace Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Use non-sparking tools

Take precautionary measures against static discharge Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

9.96 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
ACETONE	67-64-1	30 - 60
DIPHENYLMETHANEDIISOCYANAT	101-68-8	1 - 5
E		

FLANGE SEALANT 2 FL.OZ

~DIPHENYLMETHANE-4,4	5873-54-1	0.1 - 1
-DI-ISOCYANANTE ~ ETHANOL	64-17-5	0.1 - 1

Any concentration shown as a range is due to batch variation.

4. FIRST AID MEASURES

Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs; Get medical advice/attention. Wash

contaminated clothing before reuse.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms

See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Highly flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Explosion data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge

None. None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. ELIMINATE all ignition sources (no smoking,

flares, sparks or flames in immediate area). Use personal protective equipment as required.

Environmental precautions

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials

Strong oxidizing agents, Bases, Reducing agents, Amines

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
	• •	(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m³ The	
	•	acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
· ·		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
DIPHENYLMETHANEDIISOCYANA	TWA: 0.005 ppm	(vacated) Ceiling: 0.02 ppm	IDLH: 75 mg/m ³
TE	• •	regulated under Methylene	Ceiling: 0.020 ppm 10 min
101-68-8		bisphenyl isocyanate	Ceiling: 0.2 mg/m ³ 10 min
		(vacated) Ceiling: 0.2 mg/m³	TWA: 0.005 ppm
		regulated under Methylene	TWA: 0.05 mg/m ³
		bisphenyl isocyanate	-
*		Ceiling: 0.02 ppm	•
·		Ceiling: 0.2 mg/m ³	
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5	• •	TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
, ,		(vacated) TWA: 1900 mg/m ³	, and the second

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state **Appearance** Odor

Liquid Blue Ketone

Odor threshold

No information available

Property

<u>Values</u>

Remarks • Method

Hq Melting point / freezing point

Boiling point / boiling range

Flash point

No information available No information available

54 °C / 129 °F -18 °C / 0 °F

Evaporation rate

< 1

Butyl acetate = 1

Air = 1

Flammability (solid, gas)

Flammability Limit in Air Upper flammability limit:

12.8% 2.6%

Lower flammability limit: Vapor pressure

No information available

No information available

Vapor density Relative density >1 1.04

Water solubility

Partially soluble

Solubility in other solvents Partition coefficient **Autoignition temperature Decomposition temperature**

No information available No information available No information available No information available

Kinematic viscosity **Dynamic viscosity Explosive properties Oxidizing properties**

No information available No information available No information available No information available

Other Information

Softening point Molecular weight **VOC Content (%)** Density

No information available No information available

<1%

No information available No information available

10, STABILITY AND REACTIVITY

Reactivity

Bulk density

85420 - PERMA SHIELD GASKET DRESSING & **FLANGE SEALANT 2 FL.OZ**

Stable under normal conditions

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Bases, Reducing agents, Amines

Hazardous Decomposition Products

Carbon oxides

Nitrogen oxides (NOx)

Isocyanates

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

May cause sensitization by inhalation. May cause drowsiness or dizziness.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion

Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
67-64-1			
DIPHENYLMETHANEDIISOCYANA	= 31600 mg/kg (Rat) = 9200	-	= 369 mg/m³ (Rat) 4 h
TE	mg/kg (Rat)		
101-68-8			
ETHANOL	= 7060 mg/kg (Rat)	•.	= 124.7 mg/L (Rat)4 h
64-17-5			

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Chemical Name	ACGIH	IARC	NTP	OSHA
DIPHENYLMETHANEDIISO	-	Group 3	-	-
CYANATE		1		
101-68-8				
ETHANOL	A3		Known	X
64-17-5				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans

Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

85420 - PERMA SHIELD GASKET DRESSING & FLANGE SEALANT 2 FL.OZ

X - Present

Target Organ Effects

Central nervous system, Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)

14160 mg/kg

ATEmix (dermal)

665704 mg/kg

ATEmix (inhalation-dust/mist)

119.4 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

13.4675 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ACETONE 67-64-1	-0.24
ETHANOL 64-17-5	-0.32

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE	Ignitable
67-64-1	
ETHANOL	Toxic
64-17-5	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no

1133

Proper shipping name:

Adhesives, Limited Quantity (LQ)

Hazard Class
Packing Group

3 || **Emergency Response Guide**

128

Number

IATA

UN/ID no

ID 8000

Proper shipping name:

Consumer commodity

Hazard Class ERG Code

9L

IMDG

UN/ID no

1133

Proper shipping name:

Adhesives, Limited Quantity (LQ)

Hazard Class

3

Packing Group

П

EmS-No

F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA

Complies

DSL/NDSL

Complies

EINECS/ELINCS

Not determined

ENCS IECSC Not determined

KECL

Complies

Complies

PICCS

Complies

AICS

Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
DIPHENYLMETHANE DIISOCYANATE [ISOMERS AND	1.0
HOMOLOGUES] - 9016-87-9	
DIPHENYLMETHANEDIISOCYANATE - 101-68-8	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122,21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	-	RQ 5000 lb final RQ
67-64-1		+	RQ 2270 kg final RQ
DIPHENYLMETHANEDIISOCYANA	5000 lb	<u>-</u>	RQ 5000 lb final RQ
TE			RQ 2270 kg final RQ
101-68-8	· ·	·	

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
ETHANOL - 64-17-5	Carcinogen
	Developmental

• Ethanol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	Х	Х	X
DIPHENYLMETHANE DIISOCYANATE [ISOMERS AND HOMOLOGUES] 9016-87-9	х	<u>-</u>	<u>.</u>
DIPHENYLMETHANEDIISOCYANA TE 101-68-8	X	X	×
ETHANOL 64-17-5	X	X	X
~DIPHENYLMETHANE-4,4 -DI-ISOCYANANTE ~ 2536-05-2	X	-	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Flammability 3 Instability 0 Health hazards 2

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

16-May-2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet