

Page: 1/8

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017

Revision: December 05, 2017

1 Identification

- · Product identifier
- · Trade name: Slime Tire Sealant
- · Product code: SDSB-5G
- Recommended use and restriction on use
- · Recommended use: Sealant
- · Restrictions on use: No relevant information available.
- · Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

ITW Permatex Canada c/o ITW Global Brands Canada 2360 Bristol Circle, Suite 101, Oakville, ON L6H 6M5 Tel (905) 693-8900

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) 1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- Hazard statements: Not regulated.
- · Precautionary statements: Not regulated.
- Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Componen	ts:			
56-81-5	glycerol	····		
9004-34-6	cellulose		 	 _

56-81-5	glycerol						25-50%
9004-34-6	cellulose				 -		<10%
14808-60-7	quartz			 	 		<1%
A .I .!		 ·	 	 			1

Additional information:

Non-classification as a carcinogen is based on non-respirable form of product.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

- Description of first aid measures
- · After inhalation:

Respiration of particulates is unlikely during normal usage.

(Cont'd. on page 2)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017

Revision: December 05, 2017

Trade name: Slime Tire Sealant

Supply fresh air; consult doctor in case of complaints.

(Cont'd. of page 1)

After skin contact:

Clean with water and soap.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

· Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: None.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information: Cool endangered receptacles with water spray.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation.
- · Environmental precautions Avoid release to the environment.
- Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Absorb liquid components with liquid-binding material.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Open and handle receptacle with care.

Keep out of reach of children.

(Cont'd. on page 3)





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017 Revision: December 05, 2017

Trade name: Slime Tire Sealant

(Cont'd. of page 2)

(Cont'd. on page 4)

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:
- Store in cool, dry conditions in well sealed receptacles.
- Information about storage in one common storage facility: No relevant information available.
- · Specific end use(s) No relevant information available.

8 Exposure co	ontrols/personal protection
· Control paran	neters
· Components w	rith limit values that require monitoring at the workplace:
56-81-5 glycero	d
PEL (USA)	Long-term value: 15* 5** mg/m³ mist; *total dust **respirable fraction
TLV (USA)	TLV withdrawn-insufficient data human occup. exp.
EL (Canada)	Long-term value: 10* 3** mg/m³ *mist; **mist, respirable
EV (Canada)	Long-term value: 10 mg/m³
1	Long-term value: 10 mg/m³
9004-34-6 cellu	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m³
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction
EV (Canada)	Long-term value: 10 mg/m³ paper fibre, total dust
LMPE (Mexico)	Long-term value: 10 mg/m³
14808-60-7 qua	rtz
PEL (USA)	see Quartz listing
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m³ *as respirable fraction
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.10* mg/m³ *respirable fraction
LMPE (Mexico)	Long-term value: 0.025* mg/m³ A2, *fracción respirable





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017

Revision: December 05, 2017

Trade name: Slime Tire Sealant

(Cont'd. of page 3)

· Exposure controls

· Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

· Engineering controls: No relevant information available.

· Breathing equipment: Not required.

· Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

· Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection:

Not required under normal conditions of use.

Protection may be required for spills.

Information on basic physical and Appearance:	d chemical properties			
Form: Color: Odor: Odor threshold:	Pasty Different according to coloring Light Not determined.			
pH-value: Melting point/Melting range: Boiling point/Boiling range:	8.8 ± 1.0 Not determined. >104 °C (>219.2 °F)			
Flash point:	>94 °C (>201.2 °F)		*	
Flammability (solid, gaseous):	Product is not flammable.			_
Auto-ignition temperature:	>260 °C (>500 °F)			
Decomposition temperature:	Not determined.		***	
Danger of explosion:	Product does not present an exp	losion hazard.		_
Explosion limits Lower: Upper:	Not determined. Not determined.			
Vapor pressure:	Not determined.	:		_
Density: Relative density: Vapor density: Evaporation rate:	1.16 ±0.10 Not determined. Not determined.			
Solubility in / Miscibility with Water:	Fully miscible.			





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017 Revision: December 05, 2017

Trade name: Slime Tire Sealant

(Cont'd. of page 4)

- · Partition coefficient (n-octanol/water): Not determined.
- ·Viscosity

Dynamic: Kinematic: Not determined. Not determined.

Other information

No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions
- Reacts with strong acids and alkali.

Reacts with strong oxidizing agents.

- · Conditions to avoid Store away from oxidizing agents.
- · Incompatible materials Oxidizers, strong bases, strong acids
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: No sensitizing effects known.
- · IARC (International Agency for Research on Cancer):

14808-60-7 quartz

|1

· NTP (National Toxicology Program):

14808-60-7 quartz

K

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Eye contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.

(Cont'd. on page 6)





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017

Revision: December 05, 2017

Trade name: Slime Tire Sealant

(Cont'd. of page 5)

- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability The product is biodegradable after prolonged adaptation.
- Bioaccumulative potential: Does not accumulate in organisms
- · Mobility in soil: No relevant information available.
- · Additional ecological information
- General notes:

Due to available data on eliminability/decomposition and bioaccumulation potential, a prolonged damage of the environment is unlikely.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA

Not regulated.

- · UN proper shipping name
- DOT, ADR, IMDG, IATA

Not regulated.

- · Transport hazard class(es)
- DOT, ADR, IMDG, IATA
- : Class

Not regulated.

(Cont'd. on page 7)





Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017

Revision: December 05, 2017

Trade name: Slime Tire Sealant

		(Cont'd, of p	age (
Packing group DOT, ADR, IMDG, IATA	Not regulated.		
Environmental hazards Marine pollutant:	No		
Special precautions for user	Not applicable.		
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	k II of Not applicable.		

Not applicable.
15 Regulatory information
Safety, health and environmental regulations/legislation specific for the substance or mixture
· United States (USA) · SARA
· Section 302 (extremely hazardous substances):
None of the ingredients are listed.
Section 355 (extremely hazardous substances):
None of the ingredients are listed.
Section 313 (Specific toxic chemical listings):
None of the ingredients are listed.
TSCA (Toxic Substances Control Act)
All ingredients are listed.
Proposition 65 (California)
Chemicals known to cause cancer: Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.
12174-11-7 Attapulgite (Palygorskite)
14808-60-7 quartz
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.
Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.
Chemicals known to cause developmental toxicity:
None of the ingredients are listed.
EPA (Environmental Protection Agency):

None of the ingredients are listed. · IARC (International Agency for Research on Cancer):
Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied. 14808-60-7 quartz

(Cont'd. on page 8)





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 05, 2017 Revision: December 05, 2017

Trade name: Slime Tire Sealant

(Cont'd. of page 7)

· NIOSH-Ca (National Institute for Occupational Safety and Health):

14808-60-7 quartz

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision December 05, 2017 / -

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/

overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com