111-685

# **Safety Data Sheet**



Revision Number: 013.0

Issue date: 12/09/2022

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

545 Thread Sealant

Pneumatic/Hydraulic Fittings

Product type/use: Restriction of Use: Anaerobic Sealant None identified

Company address:

Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga. Ontario L5N 6C3 IDH number:

195662

Item number:

54541 Canada

Region: Contact information:

Telephone: +1 (905) 814-6511

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

WARNING:

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF CAUSING CANCER.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR

REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

Response:

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Disposal: Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

IDH number: 195662

Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings

Page 1 of 6

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*	
Polyglycol dioctanoate	18268-70-7	30 - 60	
2-Hydroxyethyl methacrylate	868-77-9	10 - 30	
Silica, amorphous, fumed, crystfree	112945-52-5	1 - 5	
Cumene hydroperoxide	80-15-9	1 - 5	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1	
methacrylic acid	79-41-4	0.1 - 1	
2-Propenoic acid, 2-methyl-, 2-(2- hydroxyethoxy)ethyl ester	2351-43-1	0.1 - 1	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

#### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic

vapours. Phenolics.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

IDH number: 195662 Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings
Page 2 of 6

Clean-up methods:

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage:

For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

Shelf Life Statement: Not available.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dioctanoate	None	None	None	None
2-Hydroxyethyl methacrylate	None	None	None	None
Silica, amorphous, fumed, crystfree	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
1-Acetyl-2-phenylhydrazine	None	None	None	None
methacrylic acid	20 ppm TWA	None	None	None
2-Propenoic acid, 2-methyl-, 2-(2- hydroxyethoxy)ethyl ester	None	None	None	None

**Engineering controls:** 

Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Liquid purple

Color: Odor:

no valuation

Odor threshold:

Not available.

IDH number: 195662

Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings Page 3 of 6

pH:

Vapor pressure:

Boiling point/range: Melting point/ range:

Specific gravity: Vapor density:

Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability: Evaporation rate:

Solubility in water: Partition coefficient (n-octanol/water):

VOC content: Viscosity:

Decomposition temperature:

Not applicable, Product is non-polar/aprotic.

< 5 mm hg (27 °C (80.6 °F)) < 0.13 mbar (20 °C (68°F))

> 150 °C (> 302°F) Not available.

1.02 > 1 20 °C

> 93 °C (> 199.4 °F) Tagliabue closed cup

Not available.

Not available. Not available.

The product is not flammable.

Not available. Slight

Not available. 1.99 %; 19.01 g/l

Not available. Not available.

## 10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of storage and use.

Hazardous reactions:

None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.

Hazardous decomposition

products:

Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Phenolics. Irritating organic vapours.

Incompatible materials:

Strong oxidizing agents. Reducing agents. Acids. Bases. Rust. Zinc. Aluminum. Iron. Copper.

Alkalis. Aldehydes. Amines. Free radical initiators. Peroxides.

Reactivity:

Not available.

Conditions to avoid:

Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

## Potential Health Effects/Symptoms

Inhalation:

Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact:

Causes skin irritation. May cause allergic skin reaction.

Eye contact:

Causes serious eye irritation.

Ingestion:

May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Polyglycol dioctanoate	None	Irritant
2-Hydroxyethyl methacrylate	Oral LD50 (Rat) = 11.2 g/kg Oral LD50 (Rat) = 5,050 mg/kg	Irritant, Allergen
Silica, amorphous, fumed, crystfree	None	No Data
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
1-Acetyl-2-phenylhydrazine	Oral LD50 (Mouse) = 270 mg/kg	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity
methacrylic acid	Oral LD50 (Mouse) = 1,332 mg/kg Oral LD50 (Mouse) = 1,600 mg/kg Oral LD50 (Mouse) = 1,250 mg/kg Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Rat) = 1,060 mg/kg Oral LD50 (Rat) = 2,224 mg/kg Dermal LD50 (Rabbit) = 500 mg/kg	Corrosive, Irritant, Allergen
2-Propenoic acid, 2-methyl-, 2-(2-hydroxyethoxy)ethyl ester	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dioctanoate	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Silica, amorphous, fumed, crystfree	No	No	No
Cumene hydroperoxide	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No
methacrylic acid	No	No	No
2-Propenoic acid, 2-methyl-, 2-(2- hydroxyethoxy)ethyl ester	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None

Packing group:

IDH number: 195662

None None

International Air Transportation (ICAO/IATA)

Product name: 545 Thread Sealant Pneumatic/Hydraulic Fittings Page 5 of 6

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None None

Packing group:

None

#### Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None None

Identification number Packing group:

None

## 15. REGULATORY INFORMATION

#### Canada Regulatory Information

**CEPA DSL/NDSL Status:** 

Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:

All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,9,11

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

12/09/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.