111-129

# **Safety Data Sheet**



**Revision Number: 008.0** 

Issue date: 06/23/2021

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric

Product type/use:

Lubricant None identified

Restriction of Use: Company address:

Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3

DANGER:

IDH number:

235092

Item number: Region:

80209 Canada

**Contact information:** 

Telephone: +1 (905) 814-6511

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
CAUSES SKIN IRRITATION.	
CAUSES SERIOUS EVE DAMAGE	

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

PICTOGRAM(S)



#### **Precautionary Statements**

Prevention:

Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face

protection.

Response:

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. Take off contaminated clothing.

Storage:

Not prescribed

Disposal:

Not prescribed

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 60	
Graphite	7782-42-5	10 - 30	

IDH number: 235092

Product name: LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric

Calcium oxide	1305-78-8	10 - 30	ŀ
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	10 - 30	
Aluminum not powder, dust or fume	7429-90-5	5 - 10	
White mineral oil (petroleum) (not cmr)	8042-47-5	1 - 5	
Quartz (SiO2) respirable particulates (RCS) >=10%	14808-60-7	0.1 - 1	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). Get medical attention. Wash clothing

before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get immediate medical attention.

Symptoms: See Section 11.

#### 5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Nor

Hazardous combustion products: Oxides of carbon. Toxic and irritating vapors.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed

container for disposal.

### 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed.

Storage: Keep in a cool, well ventilated area.

Shelf Life Statement: Not available.

IDH number: 235092 Product name: LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric Page 2 of 6

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Aluminum not powder, dust or fume	1 mg/m3 TWA Respirable fraction.	None	None	None
White mineral oil (petroleum) (not cmr)	Included in the regulation but with no data values. See regulation for further details Exposure by all routes should be carefully controlled to levels as low as possible.  5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist.	None	None
Quartz (SiO2) respirable particulates (RCS) >=10%	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: Silver

Odor: Hydrocarbon-like
Odor threshold: Not available.
pH: Not applicable
Vapor pressure: Not available.
Boiling point/range: Not available.
Melting point/ range: Not available.
Specific gravity: 1.25

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Not available.

Not available.

Not available.

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autolgnition temperature:

Flammability:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available.

Not available.

Not available.

Not available.

VOC content:

<a href="mailto:square:">< 3 %</a>

Viscosity: Not available.

Decomposition temperature: Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition Oxides

products:

Oxides of carbon. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents. Acids. Water. Alkalis. Hydrogen fluoride. Phosphorus Compounds.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:

May cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding

could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of

this product causes no such release.

Skin contact:

Causes skin irritation.

Eye contact: Ingestion: Causes serious eye damage. Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l	Irritant	
Graphite	Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3	Lung	
Calcium oxide	Inhalation LC50 (Rat, 4 h) = 40 mg/m3 Inhalation LC50 (Rat, 4 h) = 160 mg/m3	Irritant, Corrosive, Eyes	
Petroleum distillates, hydrotreated, light naphthenic	Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = 9.6 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = > 5 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l	Irritant	
Aluminum not powder, dust or fume	Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l	Central nervous system, Irritant, Lung	
White mineral oil (petroleum) (not cmr)	Inhalation LC50 (Rat, 4 h) = > 5 mg/l	No Data	
Quartz (SiO2) respirable particulates (RCS) >=10%	None	No Data	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Graphite	No	No	No
Calcium oxide	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
Aluminum not powder, dust or fume	No	No	No
White mineral oil (petroleum) (not cmr)	No	No	No
Quartz (SiO2) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	Yes

# 12. ECOLOGICAL INFORMATION

**Ecological information:** 

IDH number: 235092

Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Product name: LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric Page 5 of 6

Proper shipping name:

ame:

Hazard class or division: Identification number: Packing group: None None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Not regulated

Hazard class or division:

None

Identification number Packing group: None None

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division:

Not regulated

Hazard class or division: Identification number: Packing group: None None

None

#### 15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status:

All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,13,15

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

IDH number: 235092

06/23/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.