LCT 51043 111-240 51825. **Safety Data Sheet**



Revision Number: 010.0

Issue date: 12/07/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

LOCTITE LB N-5000 HIGH

PERFORMANCE ANTI-SEIZE known

as N-5000 High Purity Anti-Seize

Product type/use: Restriction of Use: Lubricant

None identified

Company address:

Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3 **IDH** number:

234280

Item number: Region:

51243 Canada

Contact information:

Telephone: +1 (905) 814-6511

MEDICAL EMERGÉNCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER:

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF CAUSING CANCER.

CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED

EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1





Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face

protection.

Response:

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage:

Store locked up.

IDH number: 234280

Product name: LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High

Purity Anti-Seize

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*	
White mineral oil~		30 - 60	-
Graphite	7782-42-5	10 - 30	
Nickel	7440-02-0	10 - 30	
Kaolin	1332-58-7	1 - 5	

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Aspiration may cause pulmonary edema and pneumonitis. Get medical

attention. Do not induce vomiting.

Symptoms: See Section 11.

Notes to physician: Aspiration may cause pulmonary edema or aspiration pneumonia.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, extinguishing powder, carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: None

IDH number: 234280

Hazardous combustion products: Oxides of carbon. Oxides of nickel. Oxides of aluminum. Metal vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Scrape up as much material as possible. Store in a partly filled, closed

container until disposal. Refer to Section 8 "Exposure Controls / Personal

Protection" prior to clean up.

Product name: LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High Purity Anti-Seize

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
White mineral oil~	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Nickel	1.5 mg/m3 TWA Inhalable fraction.	1 mg/m3 PEL (as Ni)	None	None
Kaolin	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None

Engineering controls:

Use positive down-draft exhaust ventilation if general ventilation is insufficient

to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection:

Safety goggles or safety glasses with side shields. Safety showers and eye

wash stations should be available.

Skin protection:

Neoprene or oil resistant gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Paste

Color:

Gray Petroleum

Odor: Odor threshold:

Not available.

pH:

Not available.

Vapor pressure: Boiling point/range: Not available. Not available.

Boiling point/range: Melting point/ range:

Not available.

IDH number: 234280

Product name: LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High Purity Anti-Seize

Specific gravity: Vapor density: Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Autoignition temperature: Flammability: Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity: Decomposition temperature: 1.2 ()GRP 1 Heavier than air. 218 °C (424.4 °F) Not available. Not available. Not available.

Slower than butyl acetate. Negligible

Not available.

Not applicable

Essentially Zero (Exempt Compounds) Not available.

Oxides of carbon. Oxides of nickel. Oxides of aluminum. Metal oxide fumes.

Not available.

10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of storage and use.

Hazardous reactions:

Will not occur.

Hazardous decomposition products:

Incompatible materials:

Strong oxidizing agents.

Reactivity:

Not available.

Conditions to avoid:

Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:

Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact:

Causes skin irritation. May cause allergic skin reaction.

Eye contact: Ingestion:

Causes serious eye irritation. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
White mineral oil~	None	Irritant
Graphite	Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3	Lung
Nickel	None	No Data
Kaolin	Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 5,000 mg/kg	Nuisance dust

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
White mineral oil~	No	No	No
Graphite	No	No	No
Nickel	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Kaolin	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

IDH number: 234280

Not available.

Product name: LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High Purity Anti-Seize

Page 4 of 6

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division:

None None

Identification number: Packing group:

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

Packing group:

None None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,15

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

IDH number: 234280

12/07/2021

Product name: LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High Purity Anti-Seize

Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 234280 Product name: LOCTITE LB N-5000 HIGH PERFORMANCE ANTI-SEIZE known as N-5000 High Purity Anti-Seize