

Safety Data Sheet



Revision Number: 003.0

Issue date: 03/30/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type:

LePage Heavy Duty Contact Cement

Not available. None identified

Restriction of Use: Company address:

Henkel Canada Corporation 2515 Meadowpine Boulevard Mississauga, Ontario L5N 6C3 IDH number:

1504724

,1504725,1504619,

Region: Canada

Contact information: Telephone: (905) 814-6511 1504629

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER:

HIGHLY FLAMMABLE LIQUID AND VAPOR.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2Δ
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	20

PICTOGRAM(S)



Precautionary Statements

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area.

Response:

Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated

clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool, Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

IDH number: 1504724

Product name: LePage Heavy Duty Contact Cement

Page 1 of 5

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

lazardous Component(s) CAS Number		Weight %*	
Acetone	67-64-1	70 - 80	
n-Butyl acetate	123-86-4	10 - 20	

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse immediately with plenty of running water, seek medical advice if

necessary.

Eye contact:

In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion:

Do not induce vomiting. Seek medical advice.

Symptoms:

See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:

Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures:

Wear self contained breathing apparatus. Wear full protective clothing.

Unusual fire or explosion hazards:

None known.

Hazardous combustion products:

None known

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow product to enter sewer or waterways.

Clean-up methods:

Soak up with inert absorbent. Store in a closed container until ready for

disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage:

Keep the container tightly closed and in a cool, well-ventilated place.

For Information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

IDH number: 1504724

Product name: LePage Heavy Duty Contact Cement

Page 2 of 5

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m3) PEL	None	None
n-Butyl acetate	50 ppm TWA 150 ppm STEL	150 ppm (710 mg/m3) PEL	None	None

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin

PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:

Odor:

Odor threshold:

pH: Vapor pressure: Boiling point/range:

Melting point/ range: Vapor density:

Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature:

Flammability: **Evaporation rate:** Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity: Decomposition temperature: Liquid

Colorless Solvent Not available.

Not available. Not available. Not available. Not available.

Not available. -22 °C (-7.6 °F) DIN 51755 Closed cup flash point

0.9 % 14.3 % Not available. Not applicable Not available.

Partially soluble Not available.

12.5 %; 111.2 g/l (by weight, calculated using CARB method; g/L less water,

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) are released.

less exempts calculated using SCAQMD method)

3,000 - 3,500 mPa.s Not available.

10. STABILITY AND REACTIVITY

Stability:

Stable at normal conditions.

Hazardous reactions:

Will not occur.

Hazardous decomposition

products:

Strong oxidizing agents.

Reactivity:

Not available.

Conditions to avoid:

Incompatible materials:

Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Eyes, Inhalation, Skin, Ingestion

IDH number: 1504724

Product name: LePage Heavy Duty Contact Cement

Page 3 of 5

Potential Health Effects/Symptoms

Inhalation:

Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.

Skin contact:

Irritating to skin.

Eye contact:

Liquid or vapors may irritate the eyes.

Ingestion: May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l	Central nervous system, Irritant
n-Butyl acetate	Oral LD50 (Rat) = 14,000 mg/kg Oral LD50 (Rat) = 14,130 mg/kg	Irritant, Central nervous system

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
n-Butyl acetate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:

ADHESIVES

Hazard class or division:

3

Identification number:

UN 1133

Packing group:

III

International Air Transportation (ICAO/IATA)

Proper shipping name:

Adhesives

Hazard class or division:

3

Identification number: Packing group:

UN 1133

Water Transportation (IMO/IMDG)

Proper shipping name:

ADHESIVES

Hazard class or division:

3

Identification number: Packing group:

UN 1133

IDH number: 1504724

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2

Prepared by:

Donna Houston, Regulatory Affairs Specialist

Issue date:

03/30/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.