

# **Safety Data Sheet**



**Revision Number: 001.2** 

Issue date: 01/16/2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type:

LePage® Poly® Spackling Compound

Water based adhesive

Restriction of Use: None identified

Company address:

Henkel Canada Corporation 2515 Meadowpine Boulevard Mississauga, Ontario L5N 6C3 IDH number:

1256114 Canada

Region: Contact information:

Telephone: +1 (800) 624-7767

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

#### HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER:

CAUSES SERIOUS EYE IRRITATION.

CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED

**EXPOSURE** 

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| EYE IRRITATION                                     | 2A              |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 1               |

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention:

Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink

or smoke when using this product. Wear eye and face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical attention if you feel unwell. If eye irritation

persists: Get medical attention.

Storage:

Disposal:

Not prescribed

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)        | CAS Number | Weight %* |  |
|-------------------------------|------------|-----------|--|
| Quartz (SiO2), <1% respirable | 14808-60-7 | 1 - 5     |  |
| Limestone                     | 1317-65-3  | 60 - 70   |  |

IDH number: 1256114

Product name: LePage® Poly® Spackling Compound

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation:

Move to fresh air in case of accidental inhalation of vapours.

Skin contact:

Wash affected area immediately with soap and water.

Eye contact:

Immediately flush eyes with plenty of water for at least 15 minutes. If

symptoms develop and persist, get medical attention.

Ingestion:

Consult a physician if necessary.

Symptoms:

See Section 11.

#### 5. FIRE FIGHTING MEASURES

Extinguishing media:

Carbon dioxide, foam, powder Water fog.

Special firefighting procedures:

Use water spray to keep fire exposed containers cool and disperse vapors.

Unusual fire or explosion hazards:

Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products:

Oxides of carbon.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** 

Not available.

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for

disposal.

# 7. HANDLING AND STORAGE

Handling:

Avoid prolonged or repeated skin contact with this material. Do not breathe

dust. Keep out of the reach of children.

Storage:

For safe storage, store at or above 0 °C (32°F)

Keep from freezing. Store in a cool, dry area. Keep containers closed when

not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)        | ACGIH TLV                               | OSHA PEL   | AIHA WEEL | OTHER |
|-------------------------------|---|--|-----------|-------|
| Quartz (SiO2), <1% respirable | 0.025 mg/m3 TWA<br>Respirable fraction. | 2.4 MPPCF TWA Respirable, 0.1 mg/m3 TWA Respirable, 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. | None      | None  |
| Limestone                     | 10 mg/m3 TWA<br>Total dust.             | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL<br>Total dust.   | None      | None  |

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection:

Respirator must be worn if exposed to dust. Use NIOSH approved respirator if there is potential to exceed exposure limit(s). When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH for dust which may be generated from this product, underlying paint, or the abrasive.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Suitable protective clothing

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:

Odor:

Odor threshold:

pH:

Vapor pressure: Boiling point/range:

Melting point/ range:

Specific gravity: Vapor density:

Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Autoignition temperature: Flammability:

Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water):

VOC content: Viscosity:

Decomposition temperature:

Paste Tan

Characteristic Not available. 8.0 - 9.0

Not available. 100 °C (212°F)no method

Not available. 1.7500 - 1.8100

Not available.

> 95 °C (> 203°F) no method; Aqueous preparation

Not available. Not available. Not available.

Not applicable 1.00 (Water = 1) Soluble

Not available. Not available. Not available. Not available.

## 10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of storage and use.

Hazardous reactions:

Will not occur.

Hazardous decomposition products:

Oxides of carbon.

Incompatible materials:

None

Reactivity:

Not available.

Conditions to avoid:

Do not freeze. Excessive heat.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Eyes, Inhalation

#### Potential Health Effects/Symptoms

Inhalation:

Dusts of this product may cause irritation of the nose, throat, and respiratory tract. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz,

a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact:

May cause slight irritation to skin.

Eye contact: Ingestion:

May cause slight irritation to eyes on contact. Not expected to be harmful by ingestion.

| Hazardous Component(s)        | LD50s and LC50s | Immediate and Delayed Health Effects                  |
|-------------------------------|-----------------|---|
| Quartz (SiO2), <1% respirable | None            | Immune system, Lung, Some evidence of carcinogenicity |
| Limestone                     | None            | Nuisance dust   |

| Hazardous Component(s)        | NTP Carcinogen                   | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|-------------------------------|----------------------------------|-----------------|--|
| Quartz (SiO2), <1% respirable | Known To Be Human<br>Carcinogen. | Group 1         | Yes                                      |
| Limestone                     | No                               | No              | No                                       |

### ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Hazard class or division: Not regulated

Identification number:

None

Packing group:

None None

IDH number: 1256114

Product name: LePage® Poly® Spackling Compound

Page 4 of 5

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number: Packing group:

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None None

Packing group:

None

### 15. REGULATORY INFORMATION

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** 

Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2,8,11,16

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

01/16/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.