



SAFETY DATA SHEET

753146 ALBERTA LTD. O/A ULTRASOL INDUSTRIES 10755-69 Avenue NW, Edmonton, Alberta T6H 2C9 Phone: 780-432-6535 Fax: 780-436-6646 E-Mail: Doktordoom@Shaw.ca www.doktordoom.com Toll Free Phone 1-800-452-0023

1. Identification

Product number

1000031968 Item #11606, 66305

Product identifier

450 G ULTRASOL DOKTOR DOOM SURFACE RESIDUAL INSECT KILLER

Company information

753146 Alberta Ltd. o/a Ultrasol Industries

10755 69th Ave NW

Edmonton, AB T6H 2C9 Canada

Company phone

1-800-452-0023

Emergency telephone US Emergency telephone outside 1-866-836-8855

US

1-952-852-4646

Version #

01

Recommended use

Pesticide

Recommended restrictions

None known.

2. Hazard(s) identification

Physical hazards

Flammable aerosols

Category 1

Health hazards

Sensitization, skin

Category 1

OSHA defined hazards

Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. May cause an allergic skin reaction.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.

Response

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards

Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, long-term hazard

Category 1

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

	Chemical name	Common nam	e and synonyms	CAS number	%
_	Butane			106-97-8	10 - 20
<u>-</u>	Propane			74-98-6	10 - 20
	Distillates (petroleum), Hydrotreated Light	· · · · · · · · · · · · · · · · · · ·		64742-47-8	2.5 - 10

Chemical name	Common name and synonyms	CAS number	%
White Mineral Oil		8042-47-5	2.5 - 10
Permethrin		52645-53-1	0.1 - 1
Other components below re	eportable levels		60 - 80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

May cause an allergic skin reaction. Dermatitis. Rash. Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Powder, Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for A Components	Air Contaminants (29 CFR 1910.1000) Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm
US. ACGIH Threshold Limit Valu	les ·	
Components	Туре	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
US. NIOSH: Pocket Guide to Cho	emical Hazards	
Components	Туре	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
•		800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Aerosol.

Color Not available.

Odor Not available.

Odor threshold

Not available.

рH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling

range

232.02 °F (111.12 °C) estimated

Flash point

-156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits Flammability limit - lower

(%)

1.9 % estimated

Flammability limit - upper

9.5 % estimated

(%)

Explosive limit - lower (%)

Explosive limit - upper (%)

Not available. Not available.

Vapor pressure

80 - 92 psig @20C estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature Decomposition temperature Not available. Not available.

Viscosity

Not available.

Other information

Explosive properties

Not explosive.

Flammability class

Flammable IB estimated

Heat of combustion (NFPA

30B)

16.15 kJ/g estimated

Oxidizing properties

Not oxidizing.

Specific gravity

0.858 estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation

No adverse effects due to inhalation are expected.

Skin contact

May cause an allergic skin reaction.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and

toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

May cause an allergic skin reaction.

Acute toxicity	May cause an allergic skin reaction.			
Components	Species	Test Results		
Butane (CAS 106-97-8)				
<u>Acute</u>				
Inhalation				
LC50	Mouse	1237 mg/l, 120 Minutes		
		52 %, 120 Minutes		
	Rat	1355 mg/l		
Distillates (petroleum), Hydrotreate				
Acute_	,			
Dermal				
LD50	Rabbit	> 2000 mg/kg		
		> 2000 mg/kg, 24 Hours		
Inhalation				
LC50	Rat	> 7.5 mg/l, 6 Hours		
		> 4.6 mg/l, 4 Hours		
O1		> 4.0 mg/l, 4 mouls		
Oral	Det	5000 mailia		
LD50	Rat	> 5000 mg/kg		
Propane (CAS 74-98-6)				
<u>Acute</u>				
Inhalation	· ·	4007 mm// 400 Minutes		
LC50	Mouse	1237 mg/l, 120 Minutes		
		52 %, 120 Minutes		
	Rat	1355 mg/l		
		658 mg/l/4h		
White Mineral Oil (CAS 8042-47-5)				
<u>Acute</u>				
Dermal		•		
LD50	Rabbit	> 2000 mg/kg, 24 Hours		
Inhalation				
LC50	Rat	2.18 mg/l, 4 Hours		
Oral				
LD50	Rat	> 5000 mg/kg		
* Estimates for product may be	e based on additional component data not shown.			
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation	o n.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritati			
Respiratory or skin sensitization				
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	May cause an allergic skin reaction.			
JAIII JUIGIILAIIVII	may sado an antigio timi readioni			

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Permethrin (CAS 52645-53-1)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Distillates (petroleum).	, Hydrotreated Ligh	t (CAS 64742-47-8)	The second secon
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Permethrin (CAS 5264	15-53-1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	0.0006 - 0.0025 mg/l, 48 hours
Fish	LC50	Apache trout (Oncorhynchus gilae	0.0013 - 0.0022 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

apache)

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butane 2.89 Permethrin 6.5 2.36 Propane

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company. Dispose of in accordance with local regulations. Empty containers or liners may retain some

Waste from residues / unused products

product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number

UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable, (each not exceeding 1 L capacity)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group

Not applicable.

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Special provisions

N82

Packaging exceptions

306

Packaging non bulk

None

Packaging bulk

None

This product meets the exception requirements of section 173,306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

UN number

UN1950

UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

Class

2.1

Subsidiary risk

Label(s)

2.1

Packing group

Not applicable.

Environmental hazards

Yes

ERG Code

101

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

Packaging Exceptions

LTD QTY

IMDG

UN number

UN1950

UN proper shipping name

AEROSOLS

Transport hazard class(es)

Class

2.1

Subsidiary risk

Label(s)

2.1

Packing group

Not applicable.

Environmental hazards

Marine pollutant

Yes F-D, S-U

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions

LTD QTY

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT

Not applicable.





IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name

CAS number

% by wt.

Permethrin

52645-53-1

0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

FIFRA Information

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The pesticide label also includes other important information, including directions for use.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)			Yes
Canada	Domestic Substances List (DSL)			No
Canada	Non-Domestic Substances List (NDSL)			No
China	Inventory of Existing Chemical Substances in China (IECSC)			Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)			No
Europe	European List of Notified Chemical Substances (ELINCS)			No
Japan	Inventory of Existing and New Chemical Substances (ENCS)			No
Korea	Existing Chemicals List (ECL)			Yes
New Zealand .	New Zealand Inventory	* *		Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)			Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory			No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-26-2018

Version #

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.