



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

136-013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name OK Autrod 316LSi

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use Arc Welding

1.3. Details of the supplier of the safety data sheet

Supplier ESAB DENTON

Street address 2800 Airport Road
Denton, TX 76207

Telephone 1-800-372-2123

Email sds.esab@esab.se

Web site www.esab.com

1.4. Emergency telephone number

Emergency phone number 1-800-372-2123

Available outside office hours No

Other

Classification(s): EN ISO 14343-A: G 19 12 3 L Si
SFA/AWS A5.9: ER316LSi

1632089820
1632099820
1632119820



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The product is not classified

2.2. Label elements

The product do not require labeling

2.3. Other hazards

This product contains nickel, which is classified as toxic by prolonged inhalation, a skin sensitizer and a suspect carcinogen. This product contains cobalt, which is possibly carcinogenic and may cause sensitization by inhalation and skin contact, and long-term adverse effects in the aquatic environment. In the form these substances are present in this product they do not contribute to a hazard classification of the product. Skin contact is normally no hazard but should be avoided to prevent possible allergic reactions.

Persons with a pacemaker should not go near welding or cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device.

When this product is used in a welding process, the most important hazards are welding fumes, heat, radiation and electric shock.

Fumes: Overexposure to welding fumes may result in symptoms like metal fume fever, dizziness, nausea, dryness or irritation of the nose, throat or eyes. Chronic overexposure to welding fumes may affect pulmonary function. Prolonged inhalation of nickel and chromium compounds above safe exposure limits can cause cancer. Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, This product contains substances that may be sensitizing.

Heat: Spatter and melting metal can cause burn injuries and start fires.

Radiation: Arc rays can severely damage eyes or skin.

Electricity: Electric shock can kill.

Other

Emergency Overview: Metal wire or rods in varying colours. This product is normally not considered hazardous as shipped. Gloves should be worn when handling to prevent cuts and abrasions.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No.	Concentration	Classification	R-phrase H-phrase
Iron	7439-89-6 231-096-4 01-2119462838 - 24	60 - 70%	- -	- -
Chromium	7440-47-3 231-157-5 -	15 - 20%	- -	- -
Nickel	7440-02-0 231-111-4 -	10 - 15%	- Carc. 2, Skin Sens. 1, STOT RE 1	- H317, H351, H372
Molybdenum	7439-98-7 231-107-2 -	2 - 5%	- -	- -
Manganese	7439-96-5 231-105-1 01-2119449803 - 34	1 - 3%	- -	- -
Silicon	7440-21-3 231-130-8 -	<1%	- -	- -
Cobalt	7440-48-4 231-158-0 -	<0,5%	- Aquatic Chronic 4, Skin Sens. 1, Resp. Sens. 1	- H317, H334, H413
Copper	7440-50-8 231-159-6 01-2119480154 - 42	<0,5%	- -	- -

Product based on This product is a continuous solid metal wire.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 4: First aid measures

4.1. Description of first aid measures

Electric shock: Disconnect and turn off the power. Use a nonconductive material to pull victim away from contact with live parts or wires. If not breathing, begin artificial respiration, preferably mouth-to-mouth.

Inhalation

If breathing has stopped, perform artificial respiration and obtain medical assistance immediately! If breathing is difficult, provide fresh air and call physician.

Skin contact

For skin burns from arc radiation, promptly flush with cold water. Get medical attention for burns or irritations that persist. To remove dust or particles wash with mild soap and water.

Eye contact

For radiation burns due to arc flash, see physician. To remove dusts or fumes flush with water for at least fifteen minutes. If irritation persists, obtain medical assistance.

4.2. Most important symptoms and effects, both acute and delayed

Not applicable

4.3. Indication of any immediate medical attention and special treatment needed

Not applicable

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

No specific recommendations for welding consumables. Welding arcs and sparks can ignite combustible and flammable materials. Use the extinguishing media recommended for the burning materials and fire situation.

5.2. Special hazards arising from the substance or mixture

Not applicable

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus as fumes or vapors may be harmful.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Refer to section 8.

6.2. Environmental precautions

Refer to section 13.

6.3. Methods and material for containment and cleaning up

Solid objects may be picked up and placed into a container. Liquids or pastes should be scooped up and placed into a container. Wear proper protective equipment while handling these materials. Do not discard as refuse.

6.4. Reference to other sections

Refer to section 8/13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Handle with care to avoid stings and cuts. Wear gloves when handling welding consumables. Avoid exposure to dust. Do not ingest. Some individuals can develop an allergic reaction to certain materials. Retain all warning and identity labels.

7.2. Conditions for safe storage, including any incompatibilities

Keep separate from chemical substances like acids and strong bases, which could cause chemical reactions.

7.3. Specific end use(s)

Arc Welding



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

Use industrial hygiene monitoring equipment to ensure that exposure does not exceed applicable national exposure limits. The following limits can be used as guidance. Unless noted, all values are for 8 hour time weighted averages (TWA).

National occupational exposure limits

Ingredient	CAS no.	EC No.	Exposure limit mg/m ³ -ppm	Short-term exposure limit mg/m ³ -ppm	Ceiling exposure limit mg/m ³ -ppm	Remark	Source	Year
Nickel	7440-02-0	231-111-4	1	-	-	as Ni	OSHA	2016
Molybdenum	7439-98-7	231-107-2	5	-	-	as Mo (sol. compds)	OSHA	2016
Molybdenum	7439-98-7	231-107-2	15	-	-	as Mo, total dust (metal and insol. compds.)	OSHA	2016
Copper	7440-50-8	231-159-6	0,1	-	-	as Cu(fume)	OSHA	2016
Copper	7440-50-8	231-159-6	1	-	-	as Cu(dust,mist)	OSHA	2016
Chromium	7440-47-3	231-157-5	1	-	-	Metal	OSHA	2016
Chromium	7440-47-3	231-157-5	0,5	-	-	as Cr(Cr(II) and Cr(III) inorganic compds)	OSHA	2016
Chromium	7440-47-3	231-157-5	0,005	-	-	as Cr(VI)(water sol. and insol. inorganic compds)	OSHA	2016
Iron	7439-89-6	231-096-4	-	-	-	No PEL	OSHA	2016
Manganese	7439-96-5	231-105-1	-	-	5	as Mn (metal and fume)	OSHA	2016
Silicon	7440-21-3	231-130-8	15	-	-	Total dust	OSHA	2016
Silicon	7440-21-3	231-130-8	5	-	-	respirable fraction	OSHA	2016
Cobalt	7440-48-4	231-158-	0,1	-	-	as Co (metal dust and fume)	OSHA	2016



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

				0										
--	--	--	--	---	--	--	--	--	--	--	--	--	--	--

8.2. Exposure controls

Not applicable

Other

Avoid exposure to welding fumes, radiation, spatter, electric shock, heated materials and dust.

Ventilation

Ensure sufficient ventilation, local exhaust, or both, to keep welding fumes and gases from breathing zone and general area. Train welders to avoid contact with live electrical parts and insulate conductive parts. Check condition of protective clothing and equipment on a regular basis.

Personal protective equipment

Use respirator or air supplied respirator when welding or brazing in a confined space, or where local exhaust or ventilation is not sufficient to keep exposure values within safe limits. Use special care when welding painted or coated steels since hazardous substances from the coating may be emitted. Wear hand, head, eyes, ear and body protection like welders gloves, helmet or face shield with filter lens, safety boots, apron, arm and shoulder protection. Keep protective clothing clean and dry.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid, non-volatile with varying color.
Appearance, colour	Not applicable
Appearance, physical state	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable
Evaporation rate	Not applicable
Explosive properties	Not applicable
Flammability (solid, gas)	Not applicable
Flash point	Not applicable
Initial boiling point and boiling range	Not applicable
Melting point	>1000°C / >1800°F
Melting point / freezing point	Not applicable
Odour	Not applicable
Odour threshold	Not applicable
Oxidising properties	Not applicable
Partition coefficient: n-octanol / water	Not applicable
pH value	Not applicable
Relative density	Not applicable
Solubility	Not applicable
Upper / lower flammability or explosive limits	Not applicable
Vapour density	Not applicable
Vapour pressure	Not applicable
Viscosity	Not applicable

9.2. Other information

Not applicable



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

Contact with chemical substances like acids or strong bases could cause generation of gas.

10.2. Chemical stability

Chemical stability

Stable at normal conditions

10.3. Possibility of hazardous reactions

Not applicable

10.4. Conditions to avoid

Conditions to avoid

This product is only intended for normal welding purposes.

10.5. Incompatible materials

Not applicable

10.6. Hazardous decomposition products

Hazardous decomposition products

When this product is used in a welding process, hazardous decomposition products would include those from the volatilization, reaction or oxidation of the materials listed in section 3 and those from the base metal and coating.

The amount of fumes generated from this product varies with welding parameters and dimensions, but is generally no more than 5 to 10 g/kg consumable.

Fumes from this product contain compounds of the following chemical elements. The rest is not analysed, according to available standards.

Fume analysis in weight %:

Fe <40

Mn <20

Cr <15

Pb <0.1

Cu <1

Ni <10

Other

Refer to applicable national exposure limits for fume compounds, including those exposure limits for fume compounds found in Section 8.

A significant amount of the chromium in the fumes can be hexavalent chromium, which has a very low exposure limit in some countries. Manganese and nickel have low exposure limits, in some countries, that may be easily exceeded.

Reasonably expected gaseous products would include carbon oxides, nitrogen oxides and ozone. Air contaminants around the welding area can be affected by the welding process and influence the composition and quantity of fumes and gases produced.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on toxicological effects	Inhalation of welding fumes and gases can be dangerous to your health. Classification of welding fumes is difficult because of varying base materials, coatings, air contamination and processes.
Acute toxicity	Acute toxicity: Overexposure to welding fumes may result in symptoms like metal fume fever, dizziness, nausea, dryness or irritation of the nose, throat or eyes.
Skin corrosion/irritation	Not applicable
Serious eye damage/irritation	Not applicable
Respiratory/skin sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Genotoxicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
STOT-single exposure	Not applicable
STOT-repeated exposure	Not applicable
Aspiration hazard	Not applicable

Other

Long term effect	Chronic toxicity: Overexposure to welding fumes may affect pulmonary function. Prolonged inhalation of nickel and chromium compounds above safe exposure limits can cause cancer. Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, Cobalt may cause cancer and sensitization by inhalation and skin contact.
-------------------------	---



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 12: Ecological information

12.1. Toxicity

Not applicable

12.2. Persistence and degradability

Not applicable

12.3. Bioaccumulative potential

Not applicable

12.4. Mobility in soil

Not applicable

12.5. Results of PBT and vPvB assessment

Not applicable

12.6. Other adverse effects

Not applicable

Other

Welding consumables and materials could degrade/weather into components originating from the consumables or from the materials used in the welding process. Avoid exposure to conditions that could lead to accumulation in soils or groundwater. This product contains cobalt, which may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal and local regulations. Use recycling procedures if available. USA RCRA: Unused products or product residue containing chromium is considered hazardous waste if discarded, RCRA ID Characteristic Toxic Hazardous Waste D007. Residues from welding consumables and processes could degrade and accumulate in soils and groundwater.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 14: Transport information

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations, limitations and legal regulations

Canada: WHMIS classification: Class D; Division 2, Subdivision A Canadian Environmental Protection Act (CEPA): All constituents of this product are on the Domestic Substance List (DSL).
 USA: Under the OSHA Hazard Communication Standard, this product is considered hazardous.
 USA: This product contains or produces a chemical known to the state of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code § 25249.5 et seq.)
 United States EPA Toxic Substance Control Act: All constituents of this product are on the TSCA inventory list or are excluded from listing.
 CERCLA/SARA Title III Reportable Quantities (RQs) and/or Threshold Planning Quantities (TPQs): : Product is a solid solution in the form of a solid article.
 - Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center and to your Local Emergency Planning Committee.
 Section 311 Hazard Class
 As shipped: Immediate; In use: Immediate delayed
 The following metallic components are listed as SARA 313 "Toxic Chemicals" and potential subject to annual SARA 313 reporting. See Section 3 for weight percent. Chromium 1.0% de minimis concentration Manganese 1.0% de minimis concentration Nickel 0.1% de minimis concentration Cobalt 0.1% de minimis concentration Copper 1.0% de minimis concentration

15.2. Chemical safety assessment

Chemical safety assessment No

Other

Read and understand the manufacturer's instructions, your employer's safety practices and the health and safety instructions on the label. Observe any federal and local regulations. Take precautions when welding and protect yourself and others.
 WARNING: Welding fumes and gases are hazardous to your health and may damage lungs and other organs. Use adequate ventilation.
 ELECTRIC SHOCK can kill. ARC RAYS and SPARKS can injure eyes and burn skin.
 Wear correct hand, head, eye and body protection.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01

SECTION 16: Other information

Changes to previous revision

This Safety Data Sheet has been revised due to modifications to Sections 1-16.

References to key literature and data sources

Refer to ESAB "Welding & Cutting - Risks and Measures", F52-529 "Precautions and Safe Practices for Electric Welding and Cutting" and F2035 "Precautions and Safe Practices for Gas Welding, Cutting and Heating" available from ESAB, and to:

USA: Contact ESAB at www.esabna.com or 1-800 ESAB-123 if you have any questions about this SDS.

American National Standard Z49.1 "Safety in Welding and Cutting", ANSI/AWS F1.5 "Methods for Sampling and Analyzing Gases from Welding and Allied Processes", ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes", AWSF3.2M/F3.2 "Ventilation Guide for Weld Fume", American Welding Society, 550 North Le Jeune Road, Miami Florida 33135. Safety and Health Fact Sheets available from AWS at www.aws.org.

OSHA Publication 2206 (29 C.F.R. 1910), U.S. Government Printing Office, Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954

American Conference of Governmental Hygienists (ACGIH), Threshold Limit Values and Biological Exposure Indices, 6500 Glenway Ave., Cincinnati, Ohio 45211, USA.

NFPA 51B "Standard for Fire Prevention During Welding, Cutting, and Other Hot Work" published by the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169.

UK: WMA Publication 236 and 237, "Hazards from Welding Fume", "The arc welder at work, some general aspects of health and safety".

Germany: Unfallverhütungsvorschrift BGV D1, "Schweißen, Schneiden und verwandte Verfahren".

Canada: CSA Standard CAN/CSA-W117.2-01 "Safety in Welding, Cutting, and Allied Processes". This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Phrase meaning

- Aquatic Chronic 4 - Hazardous to the aquatic environment — Chronic hazard category 4
- Carc. 2 - Carcinogenicity, hazard category 2
- Resp. Sens. 1 - Respiratory sensitisation, hazard category 1
- Skin Sens. 1 - Skin sensitisation, hazard category 1
- STOT RE 1 - Specific Target Organ Toxicity — Repeated exposure, hazard category 1
- H317 - May cause an allergic skin reaction.
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H351 - Suspected of causing cancer.
- H372 - Causes damage to organs through prolonged or repeated exposure.
- H413 - May cause long lasting harmful effects to aquatic life.

Other

Additional Information

ESAB requests the users of this product to study this Safety Data Sheet (SDS) and become aware of product hazards and safety information. To promote safe use of this product a user should:
-notify its employees, agents and contractors of the information on this SDS and any product hazards/safety information.



SAFETY DATA SHEET

This Safety Data Sheet complies with Regulation (EC) No 1907/2006, 1272/2008, ISO 11014-1 and ANSI Z400.1

OK Autrod 316LSi

Issued: 2016-04-01



-furnish this same information to each of its customers for this product.
-request such customers to notify employees and customers for the same product hazards and safety information.

The information herein is given in good faith and based on technical data that ESAB believes to be reliable. Since the conditions of use is outside our control, we assume no liability in connection with any use of this information and no warranty, expressed or implied is given.
Contact ESAB for more information.