

140-031

**SAFETY DATA SHEET**

Issuing Date 17-Dec-2014

Revision Date 29-Nov-2018

Revision Number 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**GHS product identifier****Product Name** Dripless Oil Lubricant**Other means of identification****Product Code(s)** DO-18, DO-4, MO-2, MO-2A, MO-4**Synonyms** Dripless Oil Lubricant**Recommended use of the chemical and restrictions on use**

Recommended Use Penetrates quickly then converts to a full-bodied lubricant, combining the best properties of oil and grease. Lubricates, rustproofs and displaces moisture. Won't gum at -20F or drip at +200F. Outperforms common "cure-all" sprays. Suggested Applications: Hinges, joints, chains, overhead hoists, stuck nuts/bolts, locks, and instrumentation.

Uses advised against No information available

Supplier's details

Supplier Address
AGS Company
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone Number CHEM-TEL, INC.
24 Hour Emergency Contact 1-800-255-3924

2. HAZARDS IDENTIFICATION**Classification**

This product is considered hazardous by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Specific Target Organ Toxicity (Repeated Exposure)	Category 1
Aspiration Toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word**Danger****Hazard Statements**

- Causes skin irritation
- Causes serious eye irritation
- May cause genetic defects
- Suspected of causing cancer
- May cause respiratory irritation. May cause drowsiness or dizziness
- Causes damage to organs through prolonged or repeated exposure
- May be fatal if swallowed and enters airways
-
- Flammable liquid and vapor.

**Appearance** Dark amber.**Physical State** Liquid.**Odor** Solvent.**Precautionary Statements****Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wash face, hands and any exposed skin thoroughly after handling.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep cool.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- If skin irritation occurs: Get medical advice/attention.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Wash contaminated clothing before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Fire

- In case of fire: Use CO₂, dry chemical, or foam for extinction.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable.

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Dripless Oil Lubricant

Chemical Name	CAS-No	Weight %	Trade secret
Stoddard solvent	8052-41-3	60-100	*
Naphtha, petroleum, hydrodesulfurized heavy	64742-82-1	10-30	*
Aluminum iso-propoxide	555-31-7	0.1-1	*
Ethylbenzene	100-41-4	<0.2	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of necessary first-aid measures****Eye Contact**

Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If symptoms persist, call a physician.

Inhalation

Move to fresh air. If symptoms persist, call a physician. Aspiration into lungs can produce severe lung damage.

Ingestion

Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Call a physician immediately. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs, lean victim forward to reduce the risk of aspiration. Aspiration may cause pulmonary edema and pneumonitis.

Most important symptoms/effects, acute and delayed**Most Important Symptoms/Effects**

No information available.

Indication of immediate medical attention and special treatment needed, if necessary**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use: Carbon dioxide (CO₂), Dry chemical, Foam.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Flammable. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. May cause sensitization by skin contact.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Environmental Precautions

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment

A vapor suppressing foam may be used to reduce vapors.

Methods for Cleaning Up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Non-sparking tools should be used. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Use only in an area containing flame proof equipment. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid breathing vapors. Remove and wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities

Storage

Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Aluminum iso-propoxide 555-31-7	TWA: 1 mg/m ³ respirable particulate matter	-	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Calcium hydroxide 1305-62-0	TWA: 5 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ not in effect as a result of reconsideration	TWA: 5 mg/m ³
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4	TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral	TWA: 5 mg/m ³ , as oil mist, mineral	-

Appropriate engineering controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

None required for consumer use. Risk of contact, wear: Safety goggles or safety glasses with face shield.

Skin and Body Protection

None required for consumer use. Repeated or prolonged contact: Wear protective gloves/clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State	Liquid.	Appearance	Dark amber.
Odor	Solvent.	Odor Threshold	No information available.

Property	Values	Remarks/ - Method
pH	Not applicable	None known
Melting Point/Range	Not determined	None known
Boiling Point/Boiling Range	Not determined	None known
Flash Point	38.33 °C / 101 °F	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Specific Gravity	0.7963	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	Negligible	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known

Viscosity	No data available	None known
Flammable Properties	Flammable liquid.	
Explosive Properties	No data available	
Oxidizing Properties	No data available	
<u>Other information</u>		
VOC Content (%)	40	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

There is no data available for this product

There is no data available for this product. May cause irritation of respiratory tract.

Aspiration into lungs can produce severe lung damage.

Eye Contact

There is no data available for this product. Expected to be an irritant based on components

Skin Contact

There is no data available for this product. Expected to be an irritant based on components

Ingestion

There is no data available for this product. May be harmful if swallowed. Potential for aspiration if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha, petroleum, hydrodesulfurized heavy	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-
Stearic acid	-	5 g/kg (Rabbit)	-
Aluminum iso-propoxide	= 11300 mg/kg (Rat)	-	-
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Benzoic acid	= 1700 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	> 26 mg/m ³ (Rat) 1 h > 12.2 mg/L (Rat) 4 h

Calcium hydroxide	= 7340 mg/kg (Rat)	-	-
Calcium petroleum sulfonate	> 20 g/kg (Rat)	> 4000 mg/kg (Rabbit)	-
Petroleum distillates, solvent-refined heavy paraffinic	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2.18 mg/L (Rat) 4 h
Water	90 mL/kg (Rat)	-	-
Petroleum distillates, hydrotreated middle	= 7400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 4.6 mg/L (Rat) 4 h
Naphthenic acids, zinc salts	= 4920 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 11.6 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Irritation

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available.

Mutagenic Effects There is no data available for this product This product contains a substance which has been classified in the EU as mutagenic

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Reproductive Toxicity No information available.

STOT - single exposure May cause respiratory irritation May cause drowsiness or dizziness

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard Risk of serious damage to the lungs (by aspiration).

Numerical measures of toxicity - Product

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 22545 mg/kg; Acute toxicity estimate

LD50 Dermal 22545 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Naphtha, petroleum, hydrodesulfurized heavy 64742-82-1				LC50 96 h: = 2.6 mg/L (Chaetogammarus marinus)
Stearic acid 57-11-4		LC50 96 h: < 3000 mg/L semi-static (Brachydanio rerio)		
Ethylbenzene 100-41-4	EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 11 mg/L	LC50 96 h: 11.0 - 18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: 7.55 - 11 mg/L flow-through (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: 9.1 - 15.6 mg/L static (Pimephales promelas) LC50 96 h: = 9.6 mg/L static	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)

	(Pseudokirchneriella subcapitata)	(Poecilia reticulata)		
Benzoic acid 65-85-0	EC50 3 h: = 5 mg/L (Anabaena inaequalis)	LC50 96 h: = 180 mg/L (Gambusia affinis)		EC50 24 h: = 300 mg/L (Daphnia magna) EC50 48 h: = 860 mg/L Static (Daphnia magna)
Calcium hydroxide 1305-62-0		LC50 96 h: = 160 mg/L static (Gambusia affinis)		
Calcium petroleum sulfonate 61789-86-4		LC50 96 h: 1.0 - 10.0 mg/L semi-static (Pimephales promelas) LC50 96 h: 5.7 - 9.7 mg/L static (Pimephales promelas)		EC50 48 h: 6.2 - 12 mg/L (Daphnia magna)
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Petroleum distillates, hydrotreated middle 64742-46-7		LC50: 35 mg/L Pimephales promelas 96 h flow-through LC50: >10000 mg/L Pimephales promelas 96 h static		

Persistence and Degradability

No information available.

Bioaccumulation

No data is available on the product itself

Chemical Name	Log Pow
Ethylbenzene	3.2

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS**Waste Disposal Methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylbenzene - 100-41-4		Included in waste stream: F039		

14. TRANSPORT INFORMATION**DOT**

Proper shipping name	Consumer commodity
Hazard Class	ORM-D
Description	Consumer commodity, ORM-D
Emergency Response Guide Number	128

TDG

UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III

MEX

UN-Number	UN1993
-----------	--------

Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III
ICAO	
UN-Number	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III
IATA	
UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
ERG Code	3L
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III
IMDG/IMO	
UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
EmS No.	F-E, S-E
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III, (38°C c.c.)
RID	
UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III
ADR	
UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Tunnel Restriction Code	(D/E)
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III, (D/E)
ADN	
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Special Provisions	274, 601, 640E
Description	UN1993, Flammable liquid, n.o.s. (Stoddard solvent), 3, III
Limited Quantity	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylbenzene	100-41-4	<0.2	0.1
Neodecanoic acid, zinc salt	27253-29-8	0.02	1.0
Naphthenic acids, zinc salts	12001-85-3	0.02	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene	1000 lb	X	X	X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Ethylbenzene	100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Stoddard solvent	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA Health Hazard 1 Flammability 2 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazard 1 Flammability 2 Physical Hazard 0 Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501
Issuing Date 17-Dec-2014
Revision Date 29-Nov-2018
Revision Note Updated Section 15.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet