155-027

SAFETY DATA SHEET

1. Identification

Product identifier BATTERY KLEEN

Other means of identification

Product code 445
Recommended use CLEANER
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Kleen-Flo Tumbler Ind Limited

Address 75 Advance Blvd

Brampton, Ontario L6T 4N1

Canada

Telephone General Assistance 1-905-793-4311

E-mail Not available.

Emergency phone number CANUTEC: 613-996-6666

2. Hazard(s) identification

Physical hazards

Label elements

Health hazards Flammable aerosols Category 1

Germ cell mutagenicity Category 1B
Carcinogenicity Category 1A



Signal word Dange

Hazard statement Extremely flammable aerosol.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Response Wash hands after handling.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

 Chemical name
 Common name and synonyms
 CAS number
 %

 Isobutane
 75-28-5
 5-10

 Propane
 74-98-6
 1-5

Other components below reportable levels 80-100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Product name: BATTERY KLEEN

Product #: 445 Version #: 01 Issue date: 01-18-2017

1/6

Skin contact

Eye contact Ingestion

Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists.

Most important

symptoms/effects, acute and

delayed

Rinse mouth. Get medical attention if symptoms occur. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed **General information** Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Not available.

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces. SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do

not breathe fumes. Extremely flammable aerosol.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components Value Type

1000 ppm Isobutane (CAS 75-28-5) STEL SDSCANADA Product name: BATTERY KLEEN

Product #: 445 Version #: 01 Issue date: 01-18-2017 2/6

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components Type Value

Propane (CAS 74-98-6) TWA 1000 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components Type Value

Isobutane (CAS 75-28-5) STEL 1000 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components Type Value

Isobutane (CAS 75-28-5) TWA 800 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components Type Value

Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range 192.94 °F (89.41 °C) estimated

Flash point -99.4 °F (-73.0 °C) PROPELLANT estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient

(n-octanol/water) Not available.

Auto-ignition temperature 860 °F (460 °C) estimated **Decomposition temperature** Not available.

Other information

Viscosity

Not explosive. **Explosive properties** Not oxidizing. **Oxidizing properties** Specific gravity 1.031 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

Not available.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidizing agents. Nitrates. Fluorine. Chlorine. Incompatible materials Hazardous decomposition No hazardous decomposition products are known. products

11. Toxicological information

Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation Skin contact No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species		Test Results
Isobutane (CAS 75-28-5)			
<u>Acute</u>		16명 1일 1일 16명	
Inhalation			가는 회가 중요 중요하다는 항상 이 강성이다.
LC50	Mouse	어느 발생 보지를 받았다면 되었다.	1237 mg/l, 120 Minutes
마양종(명조로 등 시간)			52 %, 120 Minutes
	Rat		1355 mg/l
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse		1237 mg/l, 120 Minutes
		시험, 하시아 설립의 영영, 반	52 %, 120 Minutes
	Rat	보면 가는 것이 되었다. 아들이 없는데	1355 mg/l
			658 mg/l/4h
1000 年 11.数 网络大型 (12.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.			어느 아내는 이 전에 되었다면 가게 되지 않아 되었다.

^{*} Estimates for product may be based on additional component data not shown.

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation

Product name: BATTERY KLEEN

SDSCANADA Product #: 445 Version #: 01 Issue date: 01-18-2017

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

This product is not expected to cause reproductive or developmental effects. Not classified.

mutagenic or genotoxic.

Carcinogenicity

Not available.

Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not an aspiration hazard.

Aspiration hazard

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Propane

2.76

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number

UN proper shipping name

UN1950

Transport hazard class(es)

AEROSOLS, flammable

Class

Subsidiary risk

Packing group

Environmental hazards

Not applicable.

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

This product is exempted under TDG section 1.17 as a limited quantity and may be shipped as a limited quantity.

SDSCANADA Product name: BATTERY KLEEN 5/6 Product #: 445 Version #: 01 Issue date: 01-18-2017

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name On inventory (ye	On inventory (yes/no)*	
Australia	Australian Inventory of Chemical Substances (AICS)	No	
Canada	Domestic Substances List (DSL)	No	
Canada	Non-Domestic Substances List (NDSL)	No	
China	Inventory of Existing Chemical Substances in China (IECSC)	No	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No	
Korea	Existing Chemicals List (ECL)	No	
New Zealand	New Zealand Inventory	No	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No	
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes	
*A "Yes" indicates that all compo	pents of this product comply with the inventory requirements administered by the governing country(s)		

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date

01-18-2017

Version#

Guidelines for SDS use: The product described in this SDS is a consumer product. It is safe for use by consumers as described on the product label under normal foreseeable conditions. This SDS is designed to provide additional valuable safety and handling information.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Product and Company Identification: Alternate Trade Names

SDSCANADA Product name: BATTERY KLEEN 6/6 Version #: 01 Issue date: 01-18-2017 Product #: 445