

155-051

# Black Tire Lube Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 07/28/2017      Revision date: 07/28/2017      Version: 1.0

## SECTION 1: Identification

### 1.1 Identification

Product form : Mixture  
Product name : Black Tire Lube  
Product code : 574, 575

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Tire Mounting Lubricant/5th wheel grease

### 1.3 Details of the supplier of the safety data sheet

**Supplier**  
Kleen-Flo Tumbler Industries Ltd.  
75 Advance Blvd.  
Brampton, L6T 4N1 - Canada  
T (905) 793-4311

### 1.4 Emergency telephone number

Emergency number : CANUTEC 613-996-6666

## SECTION 2: Hazard identification

### 2.1 Classification of the substance or mixture

GHS classification  
Eye Irrit. 2B

### 2.2 Label elements

#### GHS labelling

Signal word (GHS) : Warning  
Hazard statements (GHS) : Causes eye irritation  
Precautionary statements (GHS) : Wash hands, forearms and face thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention

### 2.3 Other hazards

No additional information available

### 2.4 Unknown acute toxicity

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Name	Product Identifier	%
Distillates, petroleum, solvent-dewaxed heavy paraffinic	(CAS-No.) 64742-65-0	80-100
Graphite	(CAS-No.) 7782-42-5	7-13

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.  
First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.  
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

# Black Tire Lube

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : Causes eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media : None known.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.
- Reactivity : No dangerous reactions known under normal conditions of use.

### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ensure adequate ventilation. Avoid contact with skin and eyes.

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

If large quantities enter a waterway, advise local authorities. Do not allow to enter into surface water or drains. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Use only in well ventilated areas.
- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a cool, well-ventilated place. Store away from heat. Keep away from strong oxidizers. Keep away from sources of ignition.

# Black Tire Lube

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)		
Not applicable		
Graphite (7782-42-5)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (all forms except graphite fibers-respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (synthetic-total dust) 5 mg/m <sup>3</sup> (synthetic-respirable fraction)
IDLH	US IDLH (mg/m <sup>3</sup> )	1250 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (natural-respirable dust)

#### 8.2 Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Neoprene rubber gloves.
Eye protection	: Wear eye/face protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feeding stuffs. Take off immediately all contaminated clothing.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	: paste
Appearance	: paste
Colour	: Dark grey, Black
Odour	: Petroleum odor.
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 399 °F (COC Method)
Relative evaporation rate (butylacetate=1)	: < 1
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 1 (air=1)
Relative density	: 0.91
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: Not explosive, may form harmful air/vapor mixtures when heated.
Oxidising properties	: No data available

# Black Tire Lube

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Flammables. Ignition sources. Incompatible materials.

### 10.5. Incompatible materials

Oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral rat	> 15000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	> 2400 mg/m <sup>3</sup> (Exposure time: 4 h)

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Causes eye irritation.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified.

STOT-single exposure : Not classified.

STOT-repeated exposure : Not classified.

Aspiration hazard : Not classified.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : Causes eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: <i>Oncorhynchus mykiss</i> )
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: <i>Daphnia magna</i> )

# Black Tire Lube

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 12.2. Persistence and degradability

#### Black Tire Lube

Persistence and degradability : Not established.

### 12.3. Bioaccumulative potential

#### Black Tire Lube

Bioaccumulative potential : Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

## SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

Not regulated

## SECTION 15: Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Revision date : 07/28/2017

Other information : None.

Prepared by : Kleen-Flo Tumbler Ind. Ltd.

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*