

SAFETY DATA SHEET

155-059

1. Identification

Product identifier PWD NON-FLAMMABLE WITH PTFE
Other means of identification
Product code 661
Recommended use coating
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Kleen-Flo Tumbler Ind Limited
Address 75 Advance Blvd
Brampton, Ontario L6T 4N1
Canada
Telephone 1-905-793-4311
E-mail Not available.
Emergency phone number CANUTEC 1-613-996-6666

Supplier Not available.

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas
Health hazards Carcinogenicity Category 1B
Label elements



Signal word Danger
Hazard statement Contains gas under pressure; may explode if heated. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
Response IF exposed or concerned: Get medical advice/attention.
Storage Store locked up. Protect from sunlight. Store in a well-ventilated place.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
Hazardous to the aquatic environment, long-term hazard Category 3

Other hazards None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Perchloroethylene		127-18-4	80-100
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	0.5-1.5

Chemical name	Common name and synonyms	CAS number	%
Petrolatum		8009-03-8	0.5-1.5
Carbon Tetrachloride		56-23-5	0.1-1
Other components below reportable levels			1-5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No specific first aid measures noted.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center.
Most important symptoms/effects, acute and delayed	Headache. Dizziness. Nausea.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Value

Components	Type	Value
Carbon Tetrachloride (CAS 56-23-5)	STEL	10 ppm
	TWA	5 ppm
Perchloroethylene (CAS 127-18-4)	STEL	100 ppm
	TWA	25 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Carbon Tetrachloride (CAS 56-23-5)	STEL	63 mg/m ³
	TWA	10 ppm 31 mg/m ³
Perchloroethylene (CAS 127-18-4)	STEL	5 ppm 678 mg/m ³
	TWA	100 ppm 170 mg/m ³ 25 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Carbon Tetrachloride (CAS 56-23-5)	TWA	2 ppm
Perchloroethylene (CAS 127-18-4)	STEL	100 ppm
	TWA	25 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Carbon Tetrachloride (CAS 56-23-5)	STEL	10 ppm
	TWA	5 ppm
Perchloroethylene (CAS 127-18-4)	STEL	100 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
	TWA	25 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Carbon Tetrachloride (CAS 56-23-5)	STEL	3 ppm
	TWA	2 ppm
Perchloroethylene (CAS 127-18-4)	STEL	100 ppm
	TWA	25 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Carbon Tetrachloride (CAS 56-23-5)	STEL	63 mg/m3
	TWA	10 ppm 31 mg/m3
Perchloroethylene (CAS 127-18-4)	STEL	5 ppm 685 mg/m3
	TWA	100 ppm 170 mg/m3 25 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Perchloroethylene (CAS 127-18-4)	0.5 mg/l	Tetrachloroethylene	Blood	*
	3 ppm	Tetrachloroethylene	End-exhaled air	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

Carbon Tetrachloride (CAS 56-23-5) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Carbon Tetrachloride (CAS 56-23-5) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Carbon Tetrachloride (CAS 56-23-5) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Carbon Tetrachloride (CAS 56-23-5) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Carbon Tetrachloride (CAS 56-23-5) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Carbon Tetrachloride (CAS 56-23-5) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Skin protection

Hand protection

Chemical respirator with organic vapor cartridge and full facepiece.
Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Respiratory protection

Thermal hazards

Wear suitable protective clothing. Use of an impervious apron is recommended.
Chemical respirator with organic vapor cartridge and full facepiece.
Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Aerosol. Compressed gas.
Color	Not available.
Odor	Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 239.55 °F (115.31 °C) estimated

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 28.79 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 1250.6 °F (677 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 1.60 g/cm³ estimated

Explosive properties Not explosive.

Heat of combustion 0.38 kJ/g estimated

Heat of combustion (NFPA 30B) 0.04 kJ/g estimated

Oxidizing properties Not oxidizing.

Percent volatile 95.39 % estimated

Specific gravity 1.599 estimated

VOC (Weight %) 95.39 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat. Contact with incompatible materials.

Incompatible materials
Hazardous decomposition
products

Strong oxidizing agents.
Hydrogen chloride.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.
Skin contact No adverse effects due to skin contact are expected.
Eye contact Direct contact with eyes may cause temporary irritation.
Ingestion Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics Headache. Dizziness. Nausea.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)		
<u>Acute</u>		
Dermal LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
Inhalation LC50	Rat	2.18 mg/l, 4 Hours
Oral LD50	Rat	> 2000 mg/kg
Perchloroethylene (CAS 127-18-4)		
<u>Acute</u>		
Inhalation LC50	Dog; Mouse; Rabbit; Rat	3000 ppm
Oral LD50	Cat; Dog; Mouse; Rabbit; Rat Rat	> 1500 mg/kg 3005 mg/kg
Petrolatum (CAS 8009-03-8)		
<u>Acute</u>		
Dermal LD50	Rabbit Rat	> 2000 mg/kg, 24 Hours > 2000 mg/kg, 24 Hours
Oral LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.
Skin sensitization This product is not expected to cause skin sensitization.
Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity May cause cancer.

ACGIH Carcinogens

~~Carbon Tetrachloride (CAS 56-23-5)~~

~~A2 Suspected human carcinogen.~~

Product name: PWD NON-FLAMMABLE WITH PTFE

Product #: 661 Version #: 01 Issue date: 08-25-2017

SDS CANADA

6 / 10

Perchloroethylene (CAS 127-18-4)

A3 Confirmed animal carcinogen with unknown relevance to humans.

Canada - Alberta OELs: Carcinogen category

Carbon Tetrachloride (CAS 56-23-5)

Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

CARBON TETRACHLORIDE (CAS 56-23-5)

Suspected human carcinogen.

TETRACHLOROETHYLENE (CAS 127-18-4)

Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

Carbon Tetrachloride (CAS 56-23-5)

Suspected carcinogenic effect in humans.

Perchloroethylene (CAS 127-18-4)

Detected carcinogenic effect in animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Tetrachloride (CAS 56-23-5)

2B Possibly carcinogenic to humans.

Perchloroethylene (CAS 127-18-4)

2A Probably carcinogenic to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects. Not classified.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Components

Harmful to aquatic life with long lasting effects.
Species

Test Results

Carbon Tetrachloride (CAS 56-23-5)

Aquatic

Fish

LC50

Fathead minnow (*Pimephales promelas*) 9.68 - 11.3 mg/l, 96 hours

Perchloroethylene (CAS 127-18-4)

Aquatic

Crustacea

EC50

Daphnia

7.55 mg/L, 48 Hours

Fish

LC50

Water flea (*Daphnia magna*)

6.1 - 9 mg/l, 48 hours

Rainbow trout, donaldson trout
(*Oncorhynchus mykiss*)

4.82 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Carbon Tetrachloride

2.83

Perchloroethylene

3.4

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information**TDG**

UN number	UN1950
UN proper shipping name	AEROSOLS (PERCHLOROETHYLENE)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-

Special precautions for user
Read safety instructions, SDS
and emergency procedures
before handling.

This product is exempted under TDG
section 1.17 as limited quantity and
can be shipped as limited quantity.

15. Regulatory information**Canadian regulations****Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Carbon Tetrachloride (CAS 56-23-5)

Restricted substance.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Carbon Tetrachloride (CAS 56-23-5)

Group II Annex B 1.1

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date 08-25-2017

Version # 01

Guidelines for SDS use: The product described in this SDS is a consumer product. It is safe for use by consumers as described on the product label under normal foreseeable conditions. This SDS is designed to provide additional valuable safety and handling information.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.