KLEEN-FLO TUMBLER INDUSTRIES LIMITED			MATERIAL SAFETY DATA SHEET				
SECTION I-MATERIAL IDEN	TIFICATION AND	<u>USE</u>					
Material Name/Identifier:	Diesel Lubricant		Stock No.			953	
Manufacturer's Name:	Kleen-Flo Tumbler Industries Ltd		Street Address:			75 Advance Blvd.	
City:	Brampton		Province:			Ontario	
Postal Code:	L6T 4N1		Emergency Phone #: CANUTEC:-			613-996-6666 (24HR)	
Chemical Name:	mixture (N.Ap.)		Chemical Family:			mixture (N.Ap.)	
Chemical Formula:	mixture (N.Ap.)		Trade Names & Synonyms:			None	
Material Use:	Diesel fuel additive		Molecular Weight:			mixture	
SECTION II-HAZARDOUS IN	GREDIENTS OF MA	ATERIAL					
Hazardous		Approximate	LD50		LC50		
Ingredients	C.A.S.	Concentration	Species & Route		Species & Route		
Naphthenic Oil	64742-53-6	30-60%	>2000 mg/kg rat-oral		N/Av.		
Petroleum Distillate	8008-20-6	30-60%	>5000mg/kg rat oral		>5000g/m3 rat-inh.		
Petroleum Naphtha	64742-94-5	10-30%	3000mg/kg rat-oral		3800mg/m3 rat-inhal,		
Naphthalene	91-20-3	1-5%	490mg/kg rat-oral		340mg/m3 rat-inhal		
1,2,4 Trimethylbenzene	95-63-6	0.1 - 1 %	N/Av.		N/Av.		
Physical State:	liquid	Odour/Appearance:	Aromatic odor/clear ligh		yellow		
Specific Gravity:	0.85	Odor Threshold(p.p.m.	): N/Av.				
Boiling Point:	82-137°C	Evaporation Rate:		N/Av.			
Freezing Point:	>-40°C	Solubility in Water:		nil			
% Volatile(by volume):	N/Av.	Vapor Pressure(mm)H		N/Av.			
Vapor Density(Air=1):	N/Av.	Coefficient of Water/O	il Distribut:	N/E			
pH:	N.Ap.						
SECTION IV-FIRE AND EXP	OSION HAZARD O	<u>F MATERIAL</u>					
Flammability Yes/No	Yes		If yes under which conditions: Heat, Op			n flame, Spark	
Auto Ignition Temperature:	N/Av.		Means of Ex	on dioxide, alcohol foam			
Flashpoint and Method:	62°C TCC		Hazardous (	Combustion P	roducts: Carbo	on dioxide, carbon monoxid	
			Aldehydes, ketones.				
Upper Flammable limit (%vol)	N/E	Lower Flammable Limit (% by volume): N/E					
Explosion Data:	Sensitivity to mecha	Sensitivity to Static: No					
SECTION V-REACTIVITY DA	ATA						
Chemical Stability Yes/No:		Yes	If NO under which conditions?: N.Ap.				
Incompatibility to Other Substances Yes/No:		Yes	If so which ones? strong oxidizing materials & acids				
Reactivity and under what cond	itions?	It may react with alum	inum at high t	emperature.			
Hazardous Decomposition Prod	ucts:	Carbon monoxide, carl	bon dioxide, alc	lehyde, ketone	es are produce	d on combustion.	
N/E: not established		N/Ap.:not applicable		=		N/Av.: not available	

Material Name/Identifier:	Diesel Lubricant	Stock No.	953	PAG	<u>E 2</u>			
SECTION VI-TOXICOLOGIC	CAL PROPERTIES OF PRODUCT			•				
Route of Entry: ALL Routes	-SKIN CONTACT -SKIN ABSORPTION	-EYE CONTACT -INI	IALATIONINC	ESTION				
Effects of Acute Exposure:	Skin and eye irritant. Can cause conjunctivitis (eyes). Prolonged and repeated contact							
	with skin can cause defatting and drying of the skin resulting in possible skin dermatitis.							
	High concentration inhalation may cause headaches, nausea, dizziness, drowsiness and central							
	nervous system depression.							
Effects of chronic exposure:	Not known							
Irritancy of Product:	Skin and eye irritation	Exposure	limit of Product:	N/E				
Sensitization of Product:	N/E	Toxicologically Synerg	stic Materials:	N/Av.	_			
-CARCINOGENICITY -RE	PRODUCTIVE EFFECTS –TERATOGENIC	TY -MUTAGENICITY	·		_			
Naphthalene has been classifie	d by International Agency for Research on Can	cer(IARC) as possible h	ıman carccinogen	(Gr.2B)				
SECTION VII-PREVENTIVE	MEASURES							
Personal Protective Equipment	to be used:				$\dashv$			
Gloves(specify):	Chemical resistant gloves	Eye (specify):	chemical safe	ty glasses	$\dashv$			
Respiratory(specify):	organic vapor mask	Clothing:	long sleeves s		<del>-</del>			
Respiratory Protection:	If used indoors or on a continuous basis, use	of NIOSH approved car	tridge type respir	tor is recommended	<del></del>			
Engineering Controls:	If used indoors or on a continuous basis, maintain exposure limit by using adequate ventilation.							
Leak and Spill Procedure:	Use non-reactive absorbent material and non sparking tools to contain spills.							
	Incase of large spill use explosion proof and grounded equipments. Prevent from entering waterways.							
Waste Disposal:	Dispose according to federal, state (Provincial) and local regulations							
Storage Requirements:	Store at cool, well ventilated area. Keep away from heat and ignition spots, open flame.							
Handling Procedures and	Handle with care. Keep away from children. Do not inhale or ingest. Avoid contact with skin and eyes.							
Equipment:		la u u coop a	001	<u>.</u>	-			
WHMIS TDG Classification	Consumer Commodity	Complies with CCCR-2	001	· ·····	┥			
DSL listing	Not Controlled Product  All components in this material are listed on the inventory.							
SECTION VIII-FIRST AID M	IEASURES							
Eye:	Flush with plenty of water for 15 minutes. Consult a physician immediately if discomfort persist.							
Skin:	Remove contaminated clothing. Wash with		•		4			
Inhalation	Move patient to fresh air and restore breathing if required. See doctor if discomfort persist.							
Ingestion:	DO NOT INDUCE VOMITING. Seek medical help immediately.							
SECTION IX-PREPARATIO	N DATE OF M.S.D.S.							
Additional Info/Comments:	<u> </u>	Sources Used: Supplie						
Phone Number:	(905) 793-4311	Prepared By: Quality		· · · · · · · · · · · · · · · · · · ·	<del> </del>			
Date Prepared:	Janaury 2, 2015.	Kleen	Flo Tumbler Ind	astries Limited	$\dashv$			
					<b>-</b>			
	HEET SUPERSEDES ANY OTHER M.S.D.S.	PREVIOUSLY PREPA						
N/Av.; not availab	le N/Ap.:not applicable	us	N/E: not esta	Disned				