

# Kleen-Loc Permanent Red Thread Locker

Revision 0

Revision date 2015-06-16

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

<b>Product name</b>	<b>Kleen-Loc Permanent Red Thread Locker</b>
<b>Stock Number</b>	<b>206/208</b>

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

<b>Product Use</b>	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC1] Adhesives, sealants;
--------------------	--

**1.3. Details of the supplier of the safety data sheet**

<b>Company Address</b>	<b>Kleen-Flo Tumbler Industries Ltd. 75 Advance Blvd. Brampton Ontario L6T 4N1</b>
<b>Web</b>	<a href="http://www.kleenflo.com">www.kleenflo.com</a>
<b>Telephone</b>	905-793-4311
<b>Fax</b>	905-793-4318

**1.4. Emergency telephone number**


<b>Emergency telephone number</b>	CANUTEC: 613-996-6666
-----------------------------------	-----------------------

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

<b>2.1.1. Classification - 1999/45/EC Main hazards</b>	<b>Xi; R36/38-43 Symbols: Xi: Irritant. Irritating to eyes and skin. May cause sensitisation by skin contact.</b>
<b>2.1.2. Classification - EC 1272/2008</b>	<b>Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319;</b>

**2.2. Label elements**

<b>Hazard pictograms</b>	
<b>Signal Word</b>	<b>Warning</b>
<b>Hazard Statement</b>	<b>Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation.</b>
<b>Precautionary Statement: Prevention</b>	<b>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.</b>

## Kleen-Loc Permanent Red Thread Locker

Revision 0

Revision date 2015-06-16

## 2.2. Label elements

<b>Precautionary Statement: Response</b>	<p>P302+P352 - IF ON SKIN: Wash with plenty of water/ .</p> <p>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P321 - Specific treatment (see on this label).</p> <p>P332+P313 - If skin irritation occurs: Get medical advice/attention.</p> <p>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P337+P313 - If eye irritation persists: Get medical advice/attention.</p>
--	---

## 2.3. Other hazards

<b>Other hazards</b>	This product does not contain any substances classified as PBT or vPvB.
----------------------	---

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19	0.5 - 1%	O; R7 T; R23 Xn; R21/22-48/20/22 C; R34 N; R51/53	
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21	40 - 50%	Xi; R43	
2-Hydroxyethyl methacrylate	607-124-00-X	868-77-9	212-782-2	01-2119490169-29	30 - 40%	Xi; R36/38 R43	
Cumene	601-024-00-X	98-82-8	202-704-5		0 - 0.5%	R10 Xn; R65 Xi; R37 N; R51/53	
p-Toluene sulfonyl hydrazide		1576-35-8	216-407-3		0 - 0.5%	T; R25 R44	
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)		128-37-0		01-2119555270-46	0 - 0.5%	R53	

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Cumene hydroperoxide	617-002-00-8	80-15-9	201-254-7	01-2119475796-19	0.5 - 1%	Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314; Aquatic Chronic 2: H411;	
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21	40 - 50%	Skin Sens. 1: H317;	
2-Hydroxyethyl methacrylate	607-124-00-X	868-77-9	212-782-2	01-2119490169-29	30 - 40%	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317;	
p-Toluene sulfonyl hydrazide		1576-35-8	216-407-3		0 - 0.5%	Flam. Liq. 3: H226; Flam. Sol 2: H228; Self-react. CD: H242; Acute Tox. 3: H301;	
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)		128-37-0		01-2119555270-46	0 - 0.5%	Aquatic Chronic 1: H410;	

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Move the exposed person to fresh air. Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if irritation or symptoms persist.
<b>Eye contact</b>	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
<b>Skin contact</b>	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Keep the affected person warm and at rest. Rinse mouth thoroughly. Drink 1 to 2 glasses of water. Seek medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
-------------------	---

# Kleen-Loc Permanent Red Thread Locker

Revision 0

Revision date 2015-06-16

## 4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Irritating to eyes.
Skin contact	Irritating to skin. Eczema. Itching.
Ingestion	Ingestion may cause nausea and vomiting.

## 4.3. Indication of any immediate medical attention and special treatment needed

	Remove the affected person from the source of contamination immediately. If you feel unwell, seek medical advice (show the label where possible).
--	---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical.
--	--

### 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

### 5.3. Advice for firefighters

	In case of fire and/or explosion do not breathe fumes. Wear. Protective equipment. Self-contained breathing apparatus. Cool fire exposed containers with waterspray.
--	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Do not allow runoff water to enter sewers or drains. Do not empty into drains; dispose of this material and its container in a safe way.
--	---

### 6.4. Reference to other sections

	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind, keeping bystanders also upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak side up to prevent escape of liquid.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Wear suitable protective clothing and gloves. Wear eye/face protection. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing. Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
--	---

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

### 7.3. Specific end use(s)

	Industrial uses: Uses of substances as such or in preparations at industrial sites.
--	---

### Suitable packaging

	LDPE Plastic containers.
--	--------------------------

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Exposure Limit Values

# Kleen-Loc Permanent Red Thread Locker



Revision 0

Revision date 2015-06-16

## 8.1.1. Exposure Limit Values

Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m <sup>3</sup> : 10
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m <sup>3</sup> : -
Cumene	WEL 8-hr limit mg/m <sup>3</sup> total - inhalable dust:	WEL 15 min limit mg/m <sup>3</sup> total - inhalable dust:
	WEL 8-hr limit mg/m <sup>3</sup> total - respirable dust:	WEL 15 min limit mg/m <sup>3</sup> total - respirable dust:
	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m <sup>3</sup> : 125
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m <sup>3</sup> : 250
	WEL 8-hr limit mg/m <sup>3</sup> total - inhalable dust:	WEL 15 min limit mg/m <sup>3</sup> total - inhalable dust:
	WEL 8-hr limit mg/m <sup>3</sup> total - respirable dust:	WEL 15 min limit mg/m <sup>3</sup> total - respirable dust:

## 8.2. Exposure controls

	 
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Wash hands at the end of each shift and before eating, smoking and using the toilet. Wash skin promptly if skin becomes contaminated. Promptly remove any clothing that has become contaminated.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Red
Odour	Characteristic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Relative density	> 1.12 (H <sub>2</sub> O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	> 400 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

# Kleen-Loc Permanent Red Thread Locker

Revision 0  
Revision date 2015-06-16

## 9.2. Other information

Conductivity	No data available
Surface tension	No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

	Avoid contact with: Copper and its alloys. Peroxides. Strong acids.
--	---

### 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

### 10.3. Possibility of hazardous reactions

	If product is contaminated and becomes unstable the product may polymerize and produce an exothermic reaction.
--	--

### 10.4. Conditions to avoid

	Heat. Keep only in the original container at a temperature not exceeding 15 °C.
--	---

### 10.5. Incompatible materials

	Acids. Copper and its alloys. Strong oxidising agents.
--	--

### 10.6. Hazardous decomposition products

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## SECTION 11: Toxicological information

### 11.1.4. Toxicological Information

2-Hydroxyethyl methacrylate	Dermal Rat LD50: >5000mg/kg	Oral Rat LD50: >5000mg/kg
Butylated Hydroxytoluene	Oral Rat LD50: 1700mg/kg	Oral Mouse LD50: 800-1600mg/kg
	Dermal Guinea Pig LD50: >8000mg/kg	
Cumene	Dermal Rat LD50: 12.3mg/kg	Oral Rat LD50: 2910mg/kg
Cumene hydroperoxide	Inhalation Rat LC50/4h: 220ppm	Oral Rat LD50: 382mg/kg
p-Toluenesulfonyl hydrazide	Oral Rat LD50: 283mg/kg	Dermal Rabbit LD50: >2000mg/kg
Triethyleneglycol Dimethacrylate	Oral Mouse LD50: >200mg/kg body weight	

## SECTION 12: Ecological information

### 12.1. Toxicity

2-Hydroxyethyl methacrylate	Algae IC50/72h: 836.0000 mg/l	Fish LC50/96h: 100.0000 mg/l
Butylated Hydroxytoluene	Daphnia EC50/48h: 1.4400 mg/l	
Cumene	Fish LC50/96h: 6.3200 mg/l	
Cumene hydroperoxide	Fish LC50/96h: 3.9000 mg/l	
Triethyleneglycol Dimethacrylate	Fish LC50/96h: 16.4 mg/l	

### 12.3. Bioaccumulative potential

#### Partition coefficient

	Kleen-Lock Permanent Thread Locker -No data available
--	---

### 12.5. Results of PBT and vPvB assessment

	The product does not contain any substances classified as PBT or vPvB.
--	--

## SECTION 13: Disposal considerations

### General Information

	Dispose of in compliance with all local and national regulations.
--	---

### Disposal methods

## Kleen-Loc Permanent Red Thread Locker

Revision 0

Revision date 2015-06-16

## Disposal methods

For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

## Disposal of packaging

Empty containers can be sent for disposal or recycling.

**SECTION 14: Transport Information**

## 14.1. UN number

The product is not classified as dangerous for carriage.

## 14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

## 14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

## 14.4. Packing group

The product is not classified as dangerous for carriage.

## 14.5. Environmental hazards

The product is not classified as dangerous for carriage.

## 14.6. Special precautions for user

The product is not classified as dangerous for carriage.

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

**SECTION 15: Regulatory Information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

**SECTION 16: Other Information**

## Other information

## Text of risk phrases in Section 3

R7 - May cause fire.  
 R10 - Flammable  
 R21/22 - Harmful in contact with skin and if swallowed.  
 R23 - Toxic by inhalation.  
 R25 - Toxic if swallowed.  
 R34 - Causes burns.  
 R36/38 - Irritating to eyes and skin.  
 R37 - Irritating to respiratory system.  
 R43 - May cause sensitisation by skin contact.  
 R44 - Risk of explosion if heated under confinement.  
 R48/20/22 - Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.  
 R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

# Kleen-Loc Permanent Red Thread Locker

Revision 0

Revision date 2015-06-16

Other information	
Text of Hazard Statements in Section 3	<p>environment.  <b>R53 - May cause long-term adverse effects in the aquatic environment.</b>  <b>R65 - Harmful: may cause lung damage if swallowed.</b></p> <p><b>Skin Sens. 1: H317 - May cause an allergic skin reaction.</b>  <b>Skin Irrit. 2: H315 - Causes skin irritation.</b>  <b>Eye Irrit. 2: H319 - Causes serious eye irritation.</b>  <b>Flam. Liq. 3: H226 - Flammable liquid and vapour.</b>  <b>Flam. Sol. 2: H228 - Flammable solid.</b>  <b>Self-react. CD: H242 - Heating may cause a fire.</b>  <b>Acute Tox. 3: H301 - Toxic if swallowed.</b>  <b>Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</b></p>
Further information	
	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>

**Guidelines for SDS use:** The product described in this SDS is a consumer product. It is safe for use by consumers as described on the product label under normal foreseeable conditions. This SDS is designed to provide additional valuable safety and handling information.