



Stock Number: PL52

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020

Supercedes: 12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

1 Identification

Product Identifier:

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A

12/1QT

Stock Number:

PL52FSPL AS-520-1

Other means of identification:

Synonyms:

No data available

Recommended use and restrictions on use:

Recommended use:

Motor Oil

Restrictions on use:

Uses other than those described above

Initial Supplier Identifier:

Warren Distribution, Inc. 950 S. 10th St., Suite 300

Omaha, NE 68108-3296

Tel No.:

+01 (800) 825-1235

+01 (402) 341-9397

Email:

sds@wd-wpp.com

Emergency telephone number and any

restrictions on the use of that number,

if applicable:

CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2 Hazard identification

Classification of the hazardous product:

Not classified under GHS

Hazard statements:

Not applicable

Other hazards known to the supplier with respect to the hazardous product:

Physical hazards not otherwise

None known.

classified

Health hazards not otherwise classified

None known.

3 Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS registry number and any unique identifiers	Concentration
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	64742-65-0	0.1 - 1
Petroleum distillates, hydrotreated heavy paraffinic	No data available	64742-54-7	5 - 10



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020

Supercedes:

12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

Highly refined synthetic base stocks	No data available	64742-54-7	80 - 100
4 First-aid measures			
Inhalation:	Remove to fresh air. If breath administer oxygen.	ng is difficult, have a tra	ained individual
Eye contact:	Use eye wash to remove a che for at least fifteen minutes. Ti transferring to the uncontami irritation persists.	It the head to prevent o	hemical from
Skin Contact:	Wash with soap and water. Go persists.	et medical attention if i	rritation develops or
Ingestion:	No hazard in normal industria attention if symptoms develo SDS.		_
The most important symptoms and effects, whether acute or delayed:	None known.		
An indication of immediate medical attention and special treatment	No additional first aid informa	tion available.	

۱ ــ						
15	Fire	-TIQ	ntır	ıg m	ıeas	ures

needed, if necessary:

Suitable extinguishing media:

Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media:

Specific hazards arising from the hazardous product, such as the nature

of any hazardous combustion:

Hazardous Combustion Products:

Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.

Carbon monoxide, Sulfur containing gases, Nitrogen containing gases,

oxides of phosphorus, Hydrogen sulfide

Special protective equipment and precautions for firefighters:

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the

surrounding fire.

No data available

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS.

Methods and materials for containment

Prevent the spread of any spill to minimize harm to human health and



Stock Number:

Date of the latest revision of the safety data sheet: 21-06-2020

Supercedes:

12-05-2020

PL52FSPL

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

and cleaning up:

the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations.

Used fluid should be disposed of at a recycling center.

7 Handling and storage

Precautions for safe handling:

Mildly irritating material. Avoid unnecessary exposure.

Conditions for safe storage:

Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Strong oxidizing agents

Incompatibility:

8 Exposure controls/personal protection

Control parameters, including occupational exposure limit values or biological limit values and the source of those values:

Canada - Alberta - Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available

Canada – British Columbia – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	0.2 mg/m3 TWA (mildly refined); 1 mg/m3 TWA (severely refined)	No data available	No data available
Petroleum distillates, hydrotreated heavy paraffinic	0.2 mg/m3 TWA (mildly refined); 1 mg/m3 TWA (severely refined)	No data available	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	No data available	No data available	No data available

Canada - Manitoba - Occupational Exposure Limits:

Chemical Name	Occupational	Occupational	Occupational
Chemical Name	Occupational		



Stock Number: PL52FSPL

Date of the latest revision of the safety data sheet: 21-06-2020

Supercedes: 12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

	Exposure Limits - TWAs	Exposure Limits - STELs	Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	No data available	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	No data available	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	No data available	No data available

Canada - New Brunswick - Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available

Canada – Newfoundland & Labrador – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	No data available	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	No data available	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	No data available	No data available

Canada – Northwest Territories – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available

Canada – Nova Scotia – Occupational Exposure Limits:

	Occupational	Occupational	Occupational
Chemical Name	Exposure Limits -	Exposure Limits -	Exposure Limits -



Stock Number:

PL52FSPL 21-06-2020

Date of the latest revision of the safety data sheet:

Supercedes:

12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

	TWAs	STELs	Ceiling	
Highly refined synthetic base stocks	5 mg/m3 TWA	No data available	No data available	
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	No data available	No data available	
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	No data available	No data available	

Canada – Nunavut – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available

Canada – Ontario – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	No data available	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	No data available	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	No data available	No data available

Canada – Prince Edward Island – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling	
Highly refined synthetic base stocks	5 mg/m3 TWA	No data available	No data available	
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	No data available	No data available	
Distillates, petroleum, solvent-	5 mg/m3 TWA	No data available	No data available	

Canada – Quebec – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits -	Occupational Exposure Limits -	Occupational Exposure Limits -
Chemical Name	TWAEVs	STEVs	Ceiling



Stock Number: PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020

Supercedes:

12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

Highly refined synthetic base stocks	No data available	No data available	No data available
Petroleum distillates, hydrotreated heavy paraffinic	No data available	No data available	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	No data available	No data available	No data available

Canada – Saskatchewan – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available

Canada - Yukon - Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Highly refined synthetic base stocks	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	10 mg/m3 STEL	No data available

Chemical Name	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL	IDLH
Highly refined synthetic base stocks	5 mg/m3 TWA	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3 TWA	5 mg/m3 TWA	10 mg/m3 STEL	No data available
Distillates, petroleum, solvent- dewaxed heavy paraffinic	5 mg/m3 TWA	5 mg/m3 TWA	10 mg/m3 STEL	No data available

Appropriate engineering controls:

Use local exhaust ventilation or other engineering controls to minimize

exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. None required where adequate ventilation is provided. If airborne

Respirator Type(s):



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020 12-05-2020

Supercedes:

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Eye and face protection:

Wear safety glasses when handling this product if there is a likelihood of

contact with eyes.

Skin Protection:

Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild

soap and water before eating, drinking, and when leaving work.

Hand protection:

Neoprene, Nitrile

General hygiene conditions:

No data available

9 Physical and chemical properties

Physical state:

Liquid

Colour:

Brown

Odour:

Mild Petroleum

Odour threshold:

Not determined

:Hq

No data available

Melting point (°C):

No data available

No data available

Freezing point (°C):

No data available

Initial boiling point and boiling range

(°C): Flash point (°C):

224

Evaporation rate:

No data available

Flammability, in the case of solids and

No data available

gases:

Upper flammable or explosive limit, %

Not established

Lower flammable or explosive limit, %

Not established

in air:

Vapour pressure:

No data available

Vapour density:

No data available

Relative density:

0.85

Solubility:

Negligible; 0-1%

Partition coefficient — n-octanol/water:

No data available

Auto-ignition temperature (°C):

No data available

Decomposition temperature (°C):

Not determined

Viscosity:

48.92

10 Stability and reactivity

Reactivity:

Chemical stability:

There are no known reactivity hazards associated with this product.

Stable under normal conditions.



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

Supercedes:

21-06-2020 12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

Possibility of hazardous reactions:

Conditions to avoid, including static

discharge, shock or vibration:

None expected under standard conditions of storage.

Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.

Moisture (will lead to product performance degradation).

Incompatible materials:

Hazardous decomposition products:

Strong oxidizing agents

Carbon monoxide Sulfur containing gases Nitrogen containing gases

oxides of phosphorus Hydrogen sulfide

11 Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Symptoms related to the physical,

chemical and toxicological

characteristics:

Eve contact, Ingestion, Inhalation, Skin contact

None known.

Immediate effects from short term exposure:

Inhalation:

Likely to be practically non-toxic based on animal data. No hazard in

normal industrial use.

Skin Contact:

This material is likely to be slightly irritating to skin based on animal data.

Can cause minor skin irritation, defatting, and dermatitis.

Eye Contact: Ingestion:

This material is likely to be non-irritating to eyes based on animal data.

Estimated to be > 5.0 g/kg. No hazard in normal industrial use.

Delayed and chronic effects from long term exposure:

Carcinogenicity:

Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

Reproductive and Developmental

Toxicity:

Not known or reported to cause reproductive or developmental toxicity.

No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

Skin Contact:

Mutagenicity:

Upon prolonged or repeated contact, can cause minor skin irritation,

defatting, and dermatitis.

Skin Absorption:

Upon prolonged or repeated exposure, no hazard in normal industrial

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Numerical measures of toxicity, including ATEs Based on available data, the classification criteria are not met.

12 Ecological information



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020 12-05-2020

Supercedes:

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

Ecotoxicity (aquatic and terrestrial, if available):

Slight ecological hazard. In high concentrations, this product may be

dangerous to plants and/or wildlife.

Ecological Toxicity Data:

Chemical Name	CAS registry number and any unique identifiers	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	EC50 (48h) Daphnia magna > 1000 mg/Ļ	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Highly refined synthetic base stocks	64742-54-7	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability:

Biodegrades slowly.

Bioaccumulative potential:

Bioconcentration may occur.

Mobility in soil:

This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects:

None known.

13 Disposal considerations

Information on safe handling for disposal and methods of disposal,

Spent or discarded material is non-hazardous according to environmental

regulations.

including any contaminated packaging:

14 Transport information

Transportation of Dangerous Goods by land (TDG):

UN number:

Not regulated for road transport

UN Proper shipping name:

Not applicable

Transport hazard class(es): Packing group:

Not applicable
Not applicable

International carriage of dangerous goods by sea (IMDG/IMO):

UN number:

Not regulated by IMDG

UN Proper shipping name:

Not applicable

Transport hazard class(es):

Not applicable

Packing group:

Not applicable

International carriage of dangerous goods by air (IATA):



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020

Supercedes:

12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

UN number:

Not regulated by IATA

UN Proper shipping name:

Not applicable

Transport hazard class(es):

Not applicable

Packing group:

Not applicable

Environmental hazards according to the

No

International Maritime Dangerous Goods Code and the United Nations

Model Regulations:

Transport in bulk (according to Annex II

No data available

of the International Convention for the Prevention of Pollution From Ships,

1973, as modified by the Protocol of 1978 (MARPOL 73/78) and the

International Code for the Construction

and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC

Code)):

Special precautions in connection with

transport or conveyance either within

or outside the premises:

No data available

15 Regulatory information

Safety, health and environmental regulations, made within or outside Canada, specific to the product in question: Canada - Domestic Substances List (DSL):

Chemical Name	CAS No	Canada - Domestic Substances List (DSL)
Highly refined synthetic base stocks	64742-54-7	Yes
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Yes
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	Yes

Canada - Non-Domestic Substances List (NDSL):

Chemical Name	CAS No	Canada - Non-Domestic Substances List (NDSL)
Highly refined synthetic base stocks	64742-54-7	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No



Stock Number: PL52FSPL

Date of the latest revision of the safety data sheet: 21-06-2020

12-05-2020

Supercedes:

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

Canada - Controlled Drugs and Substances:

Chemical Name	CAS No	Schedule I	Schedule II	Schedule III	Schedule IV	Schedule V	Schedule VII	Schedule VIII
Highly refined synthetic base stocks	64742-54-7	No	No	No	No	No	No	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No	No	No	No

Chemical Name	CAS No	Class A Precursors	Class B Precursors	Exempt Precursors	Class 1 Targeted Substances	Class 2 Targeted Substances
Highly refined synthetic base stocks	64742-54-7	No	No	No	No	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No	No

Canada - CEPA - Schedule III Export Control List:

Chemical Name	CAS No	Part 1 Prohibited Substances	Part 2 Substances Subject to Notification or Consent	Part 3 Restricted Substances	Export Control List
Highly refined synthetic base stocks	64742-54-7	No	No	No	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020

Supercedes:

12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting:

Chemical Name	CAS No	Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting
Highly refined synthetic base stocks	64742-54-7	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	No

Canada - Narcotic Control Regulations (C.R.C., c. 1041):

Chemical Name	CAS No	Canada - Narcotic Control Regulations (C.R.C., c. 1041)	
Highly refined synthetic base stocks	64742-54-7	No	
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	No	

Canada - Ontario - Toxics Reduction - List of Priority Toxics:

Chemical Name	CAS No	Canada - Ontario - Toxics Reduction - List of Priority Toxics	
Highly refined synthetic base stocks	64742-54-7	No	
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	No	

Stockholm Convention on Persistent Organic Pollutants:

Chemical Name	CAS No		Stockholm Convention on Persistent Organic Pollutants
Highly refined synthetic base stocks	64742-54-7	* .	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	*	No
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	. i.	No

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade:



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020

Supercedes:

12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

Chemical Name	CAS No		Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.
Highly refined synthetic base stocks	64742-54-7	1 1	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7		No
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0		No

(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs):

Chemical Name	CAS No	(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs)
Highly refined synthetic base stocks	64742-54-7	No .
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	No

Montreal Protocol on Substances that Deplete the Ozone Layer:

Chemical Name	CAS No	Montreal Protocol on Substances that Deplete the Ozone Layer
Highly refined synthetic base stocks	64742-54-7	No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	No

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.:

Chemical Name	CAS No		Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.
Highly refined synthetic base stocks	64742-54-7		No
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	1	No
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0		No



Stock Number:

PL52FSPL

Date of the latest revision of the safety data sheet:

21-06-2020

Supercedes:

12-05-2020

PROPEL FULL SYNTHETIC SAE 5W-20 MOTOR OIL API SP, ILSAC GF-6A 12/1QT

16 Other information

Date of the latest revision of the safety

21-06-2020

data sheet:

Revision Number:

6

Reason for revision:

Activated by Document Formulation Generation

Disclaimer:

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.