

# Safety Data Sheet



Stock Number: PL1890PL  
Date of the latest revision of the safety data sheet: 21-06-2020  
Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

### 1 Identification

**Product Identifier:** PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT  
**Stock Number:** PL1890PL  
G-8090-1

**Other means of identification:**  
**Synonyms:** No data available

**Recommended use and restrictions on use:**  
**Recommended use:** Gear Oil  
**Restrictions on use:** Uses other than those described above

**Initial Supplier Identifier:** Warren Distribution, Inc.  
950 S. 10th St., Suite 300  
Omaha, NE 68108-3296

**Tel No.:** +01 (800) 825-1235 +01 (402) 341-9397  
**Email:** sds@wd-wpp.com

**Emergency telephone number and any restrictions on the use of that number, if applicable:** CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

### 2 Hazard identification

**Classification of the hazardous product:**

Not classified under GHS

**Hazard statements:** Not applicable

**Other hazards known to the supplier with respect to the hazardous product:**

**Physical hazards not otherwise classified** None known.

**Health hazards not otherwise classified** None known.

### 3 Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS registry number and any unique identifiers	Concentration
Petroleum distillates, solvent-refined heavy paraffinic	No data available	64741-88-4	0.1 - 1
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	64742-65-0	0.1 - 1
Residual oils (petroleum), solvent	No data available	64742-62-7	10 - 30

# Safety Data Sheet



**Stock Number:** PL1890PL  
**Date of the latest revision of the safety data sheet:** 21-06-2020  
**Supercedes:** 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

dewaxed			
Petroleum distillates, hydrotreated heavy paraffinic	No data available	64742-54-7	60 - 80

### 4 First-aid measures

<b>Inhalation:</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
<b>Eye contact:</b>	Use eye wash to remove a chemical from the eye. Flush the affected eye for at least fifteen minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention if irritation persists.
<b>Skin Contact:</b>	Wash with soap and water. Get medical attention if irritation develops or persists.
<b>Ingestion:</b>	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
<b>The most important symptoms and effects, whether acute or delayed:</b>	None known.
<b>An indication of immediate medical attention and special treatment needed, if necessary:</b>	No additional first aid information available.

### 5 Fire-fighting measures

<b>Suitable extinguishing media:</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
<b>Unsuitable extinguishing media:</b>	No data available
<b>Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion:</b>	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
<b>Hazardous Combustion Products:</b>	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, oxides of phosphorus, Hydrogen sulfide
<b>Special protective equipment and precautions for firefighters:</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

### 6 Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures:</b>	No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations
---	---

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

**Methods and materials for containment and cleaning up:** found in Section 8 of this SDS.  
 No special spill clean up considerations. Collect and discard in regular trash.

### 7 Handling and storage

**Precautions for safe handling:** Mildly irritating material. Avoid unnecessary exposure.  
**Conditions for safe storage:** Store in a cool dry place. Isolate from incompatible materials.  
**Materials to Avoid/Chemical Incompatibility:** Strong oxidizing agents

### 8 Exposure controls/personal protection

Control parameters, including occupational exposure limit values or biological limit values and the source of those values:

#### Canada – Alberta – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available

#### Canada – British Columbia – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	0.2 mg/m <sup>3</sup> TWA (mildly refined); 1 mg/m <sup>3</sup> TWA (severely refined)	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	No data available	No data available

#### Canada – Manitoba – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

### Canada – New Brunswick – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available

### Canada – Newfoundland & Labrador – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available

### Canada – Northwest Territories – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available

### Canada – Nova Scotia – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available

### Canada – Nunavut – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

### Canada – Ontario – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available

### Canada – Prince Edward Island – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	No data available	No data available

### Canada – Quebec – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAEVs	Occupational Exposure Limits - STEVs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	No data available	No data available	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	No data available	No data available

### Canada – Saskatchewan – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available

### Canada - Yukon – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

Chemical Name	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL	IDLH
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m <sup>3</sup> TWA	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA	5 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup> STEL	No data available

**Appropriate engineering controls:** Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.

**Individual protection measures, such as personal protective equipment:**

**Respiratory Protection:** Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

**Respirator Type(s):** None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

**Eye and face protection:** Wear safety glasses when handling this product if there is a likelihood of contact with eyes.

**Skin Protection:** Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

**Hand protection:** Neoprene, Nitrile

**General hygiene conditions:** No data available

### 9 Physical and chemical properties

**Physical state:** Liquid  
**Colour:** Amber  
**Odour:** Mild  
 Petroleum  
**Odour threshold:** Not determined  
**pH:** No data available  
**Melting point (°C):** No data available  
**Freezing point (°C):** No data available  
**Initial boiling point and boiling range (°C):** No data available  
**Flash point (°C):** 232  
**Evaporation rate:** No data available  
**Flammability, in the case of solids and gases:** No data available  
**Upper flammable or explosive limit, % in air:** Not established

# Safety Data Sheet



Stock Number: PL1890PL

Date of the latest revision of the safety data sheet: 21-06-2020

Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

Lower flammable or explosive limit, % in air: Not established

Vapour pressure: No data available

Vapour density: No data available

Relative density: 0.88

Solubility: Insoluble

Partition coefficient — n-octanol/water: No data available

Auto-ignition temperature (°C): No data available

Decomposition temperature (°C): Not determined

Viscosity: 138.82

### 10 Stability and reactivity

Reactivity: There are no known reactivity hazards associated with this product.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None expected under standard conditions of storage.

Conditions to avoid, including static discharge, shock or vibration: Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide Sulfur containing gases Nitrogen containing gases oxides of phosphorus Hydrogen sulfide

### 11 Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact): Eye contact, Ingestion, Inhalation, Skin contact

Symptoms related to the physical, chemical and toxicological characteristics: None known.

#### Immediate effects from short term exposure:

Inhalation: Likely to be practically non-toxic based on animal data. No hazard in normal industrial use.

Skin Contact: This material is likely to be slightly irritating to skin based on animal data. Can cause minor skin irritation, defatting, and dermatitis.

Eye Contact: This material is likely to be non-irritating to eyes based on animal data.

Ingestion: Estimated to be > 5.0 g/kg. No hazard in normal industrial use.

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

### Delayed and chronic effects from long term exposure:

**Carcinogenicity:** Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.

**Reproductive and Developmental Toxicity:** Not known or reported to cause reproductive or developmental toxicity.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

**Skin Contact:** Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

**Skin Absorption:** Upon prolonged or repeated exposure, no hazard in normal industrial use.

**STOT-single exposure:** Based on available data, the classification criteria are not met.

**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

**Aspiration hazard:** Based on available data, the classification criteria are not met.

**Numerical measures of toxicity, including ATEs** Based on available data, the classification criteria are not met.

<b>12 Ecological information</b>
----------------------------------

**Ecotoxicity (aquatic and terrestrial, if available):** Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

### Ecological Toxicity Data:

Chemical Name	CAS registry number and any unique identifiers	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) > 5000 mg/L
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
(Z)-Octadec-9-enylamine	112-90-3	EC50 (48h) Daphnia magna 0.011 mg/L	Aquatic ERC50 (96h) 0.04 mg/L	LC50 (96h) 0.06 mg/L
Residual oils (petroleum), solvent dewaxed	64742-62-7	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L

**Persistence and degradability:** Biodegrades slowly.

**Bioaccumulative potential:** Bioconcentration may occur.



# Safety Data Sheet



Stock Number: PL1890PL

Date of the latest revision of the safety data sheet: 21-06-2020

Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

**Mobility in soil:** This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.

**Other adverse effects:** None known.

### 13 Disposal considerations

**Information on safe handling for disposal and methods of disposal, including any contaminated packaging:** Spent or discarded material is non-hazardous according to environmental regulations.

### 14 Transport information

#### Transportation of Dangerous Goods by land (TDG):

**UN number:** Not regulated for road transport

**UN Proper shipping name:** Not applicable

**Transport hazard class(es):** Not applicable

**Packing group:** Not applicable

#### International carriage of dangerous goods by sea (IMDG/IMO):

**UN number:** Not regulated by IMDG

**UN Proper shipping name:** Not applicable

**Transport hazard class(es):** Not applicable

**Packing group:** Not applicable

#### International carriage of dangerous goods by air (IATA):

**UN number:** Not regulated by IATA

**UN Proper shipping name:** Not applicable

**Transport hazard class(es):** Not applicable

**Packing group:** Not applicable

**Environmental hazards according to the International Maritime Dangerous Goods Code and the United Nations Model Regulations:** No

**Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78) and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)):** No data available

**Special precautions in connection with transport or conveyance either within** No data available

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

or outside the premises:

### 15 Regulatory information

Safety, health and environmental regulations, made within or outside Canada, specific to the product in question:

#### Canada - Domestic Substances List (DSL):

Chemical Name	CAS No	Canada - Domestic Substances List (DSL)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Yes
Residual oils (petroleum), solvent dewaxed	64742-62-7	Yes
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	Yes
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	Yes

#### Canada - Non-Domestic Substances List (NDSL):

Chemical Name	CAS No	Canada - Non-Domestic Substances List (NDSL)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

#### Canada - Controlled Drugs and Substances:

Chemical Name	CAS No	Schedule I	Schedule II	Schedule III	Schedule IV	Schedule V	Schedule VII	Schedule VIII
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No	No	No	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No	No	No	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No	No	No	No

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No	No	No	No	No	No	No
---	------------	----	----	----	----	----	----	----

Chemical Name	CAS No	Class A Precursors	Class B Precursors	Exempt Precursors	Class 1 Targeted Substances	Class 2 Targeted Substances
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No	No	No	No	No

### Canada - CEPA - Schedule III Export Control List:

Chemical Name	CAS No	Part 1 Prohibited Substances	Part 2 Substances Subject to Notification or Consent	Part 3 Restricted Substances	Export Control List
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No	No	No	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No	No	No	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No	No	No	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No	No	No	No

### Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting:

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supersedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

Chemical Name	CAS No	Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

### Canada - Narcotic Control Regulations (C.R.C., c. 1041):

Chemical Name	CAS No	Canada - Narcotic Control Regulations (C.R.C., c. 1041)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

### Canada - Ontario - Toxics Reduction - List of Priority Toxics:

Chemical Name	CAS No	Canada - Ontario - Toxics Reduction - List of Priority Toxics
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

### Stockholm Convention on Persistent Organic Pollutants:

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supercedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

Chemical Name	CAS No	Stockholm Convention on Persistent Organic Pollutants
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

### Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade:

Chemical Name	CAS No	Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade .
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

### (United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs):

Chemical Name	CAS No	(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs)
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

# Safety Data Sheet



Stock Number: PL1890PL  
 Date of the latest revision of the safety data sheet: 21-06-2020  
 Supersedes: 12-05-2020

## PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT

### Montreal Protocol on Substances that Deplete the Ozone Layer:

Chemical Name	CAS No	Montreal Protocol on Substances that Deplete the Ozone Layer
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

### Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.:

Chemical Name	CAS No	Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	No
Residual oils (petroleum), solvent dewaxed	64742-62-7	No
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	No
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	No

### 16 Other information

**Date of the latest revision of the safety data sheet:** 21-06-2020

**Revision Number:** 10

**Reason for revision:** Activated by Document Formulation Generation

**Disclaimer:** This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for

# Safety Data Sheet



**Stock Number:** PL1890PL  
**Date of the latest revision of the safety data sheet:** 21-06-2020  
**Supersedes:** 12-05-2020

## **PROPEL SAE 80W-90 GEAR OIL API GL-5 12/1QT**

---

the use of any product in a manner that might infringe existing patents.  
No warranty is made, either expressed or implied.