

270-057 SAFETY DATA SHEET

A CSW Industrials Company

Issuing Date 12-May-2017

Revision Date 23-May-2017

Revision Number 2

NGHS / English



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name

WRL™ AEROSOL

Other means of identification

Product Code(s)

WPS-JLI-124

Synonyms

JET-LUBE 769® AEROSOL

Recommended use of the chemical and restrictions on use

Recommended Use

Lubricants, Greases and Release Products

Uses advised against

No information available

Details of the supplier of the safety data sheet

Supplier Identification

Jet-Lube of Canada Ltd.

Address

Jet-Lube of Canada LLC 3820 - 97 Street NW Edmonton, AB. Canada

T6E 5S8

Telephone

JLC Office 1.780.463.7441 Toll Free 1.888.771,7775

E-mail

Sales@jetlubecanada.com

Emergency telephone number

Company Emergency Phone

1-800-699-6318

Number

Emergency Telephone Number

CHEMTREC: +1-703-527-3887 (INTERNATIONAL)

1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Carcinogenicity Category 1B



A	
Aspiration toxicity	Category 1
Gases Under Pressure	
	Compressed Gas

Appearance Light orange

Physical state Liquid Aerosol


Odor Petroleum

GHS Label elements, including precautionary statements

Danger

Hazard statements

May cause cancer May be fatal if swallowed and enters airways Contains gas under pressure; may explode if heated



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Toxic to aquatic life with long lasting effects

Unknown acute toxicity

100 % of the mixture consists of ingredient(s) of unknown toxicity

- 100 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 100 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance



Not applicable.

<u>Mixture</u>

Synonyms

JET-LUBE 769® AEROSOL

Chemical name	CAS-No	Percent	Hazardous Material Information Review Act registry number (HMIRA registry #)			
Petroleum distillates, hydrotreated light	64742-47-8	60-65	-	-		
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	20-25	<u>-</u>			
Carbon dioxide	124-38-9	2-5	-			

4. FIRST AID MEASURES

First aid measures

General advice

IF exposed or concerned: Get medical advice/attention. Immediate medical attention is

required. Show this safety data sheet to the doctor in attendance.

Inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Ingestion

Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the



surrounding environment.

Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the

chemical

Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact Yes. Sensitivity to Static Discharge None

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical name		ACGIH T	īV	n	SHA PEL		NIOSH IDLH
Petroleum distillates hydrotreated light 64742-47-8			g/m³ ng/m³	TWA: 5 mg/m³ (as oil mist)			Meshiden
Petroleum distillates, so dewaxed heavy paraff 64742-65-0	lvent inic	TWA: 5 mg/m³, a minera STEL: TWA: 10 m mist, mine	il ng/m³, as oil		ng/m³, as oil mist, mineral		
Carbon dioxide 124-38-9		STEL = 3000 TWA: 5000	• •	TWA: (vacated) (vacated) T (vacated) :	x: 5000 ppm 9000 mg/m ³ TWA: 10000 ppm WA: 18000 mg/m ³ STEL: 30000 ppm TEL: 54000 mg/m ³		IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³
Chemical name		Alberta	British C	olumbia	Ontario TWAE	V	Quebec
Petroleum distillates, hydrotreated light 64742-47-8				00 mg/m³ kin		·	
Carbon dioxide 124-38-9	TV ST	TWA: 5000 ppm TWA: 5 TWA: 9000 mg/m³ STEL: 19 STEL: 30000 ppm STEL: 54000 mg/m³		000 ppm 6000 ppm	TWA: 5000 pp STEL: 30000 pp		TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls

Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

If splashes are likely to occur, wear safety glasses with side-shields.

Hand protection

Wear suitable gloves.

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling

the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Appearance Odor

Liquid; Aerosol Light orange Petroleum

Color Odor Threshold No information available No information available **Property**

Melting / freezing point Boiling point / boiling range Flash Point

Evaporation Rate Flammability (solid, gas)

Flammability Limit in Air Upper flammability limit Lower flammability limit

Vapor pressure Vapor density Relative density

Water Solubility Solubility(ies)

Partition coefficient: n-octanol/water Autoignition temperature

Decomposition temperature Kinematic viscosity Dynamic viscosity **Explosive properties**

Oxidizing properties

Other Information Softening Point Molecular Weight VOC Content (%)

Liquid Density Bulk Density Particle Size

Particle Size Distribution

<u>Values</u>

-50 °C 199-260 °C > 75 °C

No data available No data available

No data available No data available No data available No data available

0.83 Slightly soluble Completely soluble

3.3 - 6

No data available No data available No data available 4.5 -6 cSt (@ 40°C) No information available No information available

No information available No information available No information available

No information available No information available No information available No information available Remarks Method

None known None known None known None known None known

None known None known

None known

None known

None known None known None known

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products Carbon oxides.

TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal. May cause irritation of respiratory tract.

Eye contact

Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact

Specific test data for the substance or mixture is not available. Repeated exposure may

cause skin dryness or cracking.

Ingestion

Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema

and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity

Acute Toxicity

Unknown acute toxicity

100 % of the mixture consists of ingredient(s) of unknown toxicity

100 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

100 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor) 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermai LD50	Inhalation LC50
Petroleum distillates, hydrotreated light	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Petroleum distillates, solvent dewaxed heavy paraffinic	-	-	>4.7 mg/l (rat) 4 hr.
Carbon dioxide	-	<u> </u>	470000 ppm (Rat)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

No information available.

Serious eye damage/eye irritation

No information available.

Respiratory or skin sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

Classification based on data available for ingredients. Contains a known or suspected

carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates,	A2	Group 1	Known	X
solvent dewaxed heavy paraffinic	•	*		
64742-65-0				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)



Group 1 - Carcinogenic to Humans NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Aspiration hazard

May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated light	•	LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss)	-	LC50 96 h: = 4720 mg/L (Den-dronereides heteropoda)
Petroleum distillates, solvent dewaxed heavy paraffinic		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)	•	EC50 48 h: > 1000 mg/L (Daphnia magna)

Persistence and Degradability

Expected to be biodegradable.

Bioaccumulation

There is no data for this product.

Mobility

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging

Do not reuse empty containers.

14. TRANSPORT INFORMATION

DOT



UN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class** 2.2

Subsidiary class

Description UN1950, Aerosols, 2.2 (8) 126

Emergency Response Guide Number

TDG

UN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class** 2.2 **Packing Group** None

Description UN1950, Aerosols, 2.2

<u>MEX</u>

UN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class** 2.2

Description UN1950, Aerosols, 2.2

ICAO

UN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class** 2.2

Description UN1950, Aerosols, 2.2

<u>IATA</u>

UN-No. UN1950

Proper Shipping Name Aerosols, non-flammable

Hazard Class 2.2 **Packing Group** None **ERG Code** 2L

Description UN1950, Aerosols, non-flammable, 2.2

IMDG/IMO

UN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class** Subsidiary class See SP63 **Packing Group** None. EmS-No. F-D, S-U

Description UN1950, Aerosols, 2.2 (See SP63)

UN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class** Classification code 5A

Description UN1950, Aerosols, 2.2

ADR/RID-Labels 2.2

<u>ADR</u>

ŪN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class** Classification code 5A **Tunnel restriction code**

Description UN1950, Aerosois, 2.2, (E)

ADR/RID-Labels

ADN

UN-No. UN1950 **Proper Shipping Name** Aerosols **Hazard Class**

Classification code

Special Provisions 190, 327, 344, 625 Description UN1950, Aerosols, 2.2

Hazard Labels 2.2 **Limited Quantity** 1 L Ventilation VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA

Contact supplier for inventory compliance status.

DSL/NDSL **EINECS/ELINCS**

Complies.

Complies. **ENCS** Not determined. KECL Not determined. **PICCS** Not determined. **AICS** Complies.

<u>Legend</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Acute Health Hazard Yes Chronic Health Hazard Yes Fire Hazard No Sudden release of pressure hazard Yes **Reactive Hazard** No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)



This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Petroleum distillates, solvent dewaxed heavy paraffinic		S			X
64742-65-0					
Carbon dioxide 124-38-9	. X	×	×	X	-

16. OTHER INFORMAT	

NFPA_

Health hazards 2

Flammability 0

Instability 0

Physical and Chemical

Chronic Hazard Star Legend

Health hazards 2*

Flammability 0 * = Chronic Health Hazard

Physical hazards 0

Properties -Personal Protection X

Prepared By

Product Stewardship

23 British American Blvd.

Latham, NY 12110 1-800-572-6501

Issuing Date

12-May-2017

Revision Date

23-May-2017

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet