



320-106
MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Dry Graphite Lube (aerosol)

Product Number (s): 75101

Product Use: Dry film lubricant

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300 (General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Vapors May Cause Flash Fires. May Cause Eye and Skin Irritation. Contents Under Pressure.
Appearance & Odor: Black liquid, ketone odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause irritation.

SKIN: May cause irritation.

INHALATION: Inhalation of solvents may cause irritation. Propellant is a simple asphyxiant.

INGESTION: May cause headache, nausea, vomiting and weakness.

CHRONIC EFFECTS: Solvents may cause defatting dermatitis.

TARGET ORGANS: None known

Medical Conditions Aggravated by Exposure: pre-existing skin conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Acetone	67-64-1	60 - 100
Isopropanol	67-63-0	1 - 5
Propane	74-98-6	10 - 30

Section 4: First Aid Measures

- Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
- Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
- Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
- Ingestion:** Do NOT induce vomiting. Get medical attention.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions. (See 16 CFR 1500.3(c)(6)). The flame extension is greater than 15 cm and less than 100 cm.

Flash Point:	-4°F / -20°C (TCC)	Upper Explosive Limit:	12.8
Autoignition Temperature:	750 - 869°F / 399 - 465°C	Lower Explosive Limit:	1.9

Fire and Explosion Data:

- Suitable Extinguishing Media:** Water, carbon dioxide, dry chemical, foam
- Products of Combustion:** Hydrocarbon fumes and smoke; carbon monoxide where combustion is incomplete
- Explosion Hazards:** Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere.
- Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

- Personal Precautions:** Use personal protection recommended in Section 8.
- Environmental Precautions:** Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.
- Methods for Containment & Clean-up:** Eliminate all sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep away from heat, sparks and open flames. Use in a well ventilated area (mechanical ventilation needed if used indoors on a continuous basis). Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing. Store away from heat, sparks and open flames.

Aerosol Storage Level: II

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Acetone	750 (v)	1000 (v)	500	750	NE		ppm
Isopropanol	400	500 (v)	200	400	NE		ppm
Propane	1000	NE	1000	NE	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVA or Viton®. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid
 Color: black
 Odor: ketone
 Odor Threshold: ND
 Specific Gravity: 0.66 – 0.70
 Initial Boiling Point: 134.6°F / 57°C
 Freezing Point: ND
 Vapor Pressure: 60 – 70 psig @ 68°F / 20°C

Vapor Density: > 1 (air = 1)
 Evaporation Rate: fast
 Solubility: ND
 Coefficient of water/oil distribution: ND
 pH: NA
 Volatile Organic Compounds: wt %: 27 g/L: 189 lbs./gal: 1.57

Section 10: Stability and Reactivity

Stability: Stable
 Conditions to Avoid: Do not use near heat, sparks, or flames.
 Incompatible Materials: Strong oxidizing agents
 Hazardous Decomposition Products: Hydrogen fumes and smoke; carbon monoxide where combustion is incomplete
 Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Acetone	5800 mg/kg	No data	50,100 mg/m ³ /8H
Isopropanol	5000 mg/kg	12,800 mg/kg	16,000 ppm/8H
Propane	No data	No data	No data

Chronic Toxicity:

Component	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	Irritant	Sensitizer
Acetone	No	No	No	E & S (moderate) / R (mild)	Yes
Isopropanol	No	No	No	E (moderate) / S (mild)	No
Propane	No	No	No	No	No

E – Eye S – Skin R - Respiratory

Reproductive Toxicity: No information available
Teratogenicity: No information available
Mutagenicity: No information available
Synergistic Effects: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available
 Persistence / Degradability: No information available
 Bioaccumulation / Accumulation: No information available
 Mobility in Environment: No information available

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is RCRA hazardous waste for the characteristic of ignitability with a waste code of D001. (See 40 CFR Part 261.20 – 261.33)
Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, flammable, 2.1, Limited Quantity

ICAO/IATA (air): UN1950, Aerosols, flammable, 2.1, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Acetone (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration (OSHA):

This product is regulated under the Hazard Communication Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: **None**

Consumer Products VOC Regulations: This product is not regulated.

State Right to Know:

New Jersey: 67-64-1, 67-63-0, 74-98-6
Pennsylvania: 67-64-1, 67-63-0, 74-98-6
Massachusetts: 67-64-1, 67-63-0, 74-98-6
Rhode Island : 67-64-1, 67-63-0, 74-98-6

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)	
Health:	2
Flammability	4
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
CRC #: 75101
Revision Date: 05/14/2015

Changes since last revision: Section 13: Disposal Considerations
Section 14: Transport Information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List
g/L: grams per Liter
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization
lbs./gal: pounds per gallon
LC: Lethal Concentration
LD: Lethal Dose

NA: Not Applicable
ND: Not Determined
NIOSH: National Institute of Occupational Safety & Health
NFPA: National Fire Protection Association
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PMCC: Pensky-Martens Closed Cup
PPE: Personal Protection Equipment
ppm: Parts per Million
RoHS: Restriction of Hazardous Substances
STEL: Short Term Exposure Limit
TCC: Tag Closed Cup
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Information System