547-007

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

LA-CO Industries, Inc.

according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 05/06/2015Revision date: 06/24/2015

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1.	Product identifier	80320	80321,	80322	80323,	80324	80325

Product form

: Mixture

80326

Trade name

: LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent

Orange, Fluorescent Yellow, Fluorescent Green

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

: Marking.

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc. 1201 Pratt Boulevard Elk Grove Village, IL. 60007-5746 Phone: (847) 956-7600 Fax: (847) 956-9885 E-mail: customer_service@laco.com

•	

1.4. Emergency telephone number

Emergency number

: 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Not classified

2.2 Label elements

GHS labelling

No labelling applicable

2.3. Other hazards

2.4 Unknown acute toxicity (GHS)

51.98 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

51.98 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

51.98 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% (w/w)	GHS classification
barium bis[2-[(2- hydroxynaphthyl)azo]naphthalenesuphon ate]	(CAS No) 1103-38-4	2.3 Red	Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 3, H412
Iron oxide red	(CAS No) 1309-37-1	2.15 Red	Aquatic Chronic 2, H411
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2- ethoxyphenyl)-3-hydroxynaphthalene-2- carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7	0.67 Purple	Skin Sens. 1, H317

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

First-aid measures after inhalation

: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.

First-aid measures after skin contact

: Wash with plenty of soap and water.

First-aid measures after eye contact

: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion

: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: No significant signs or symptoms indicative of any health hazard are expected to occur.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Carbon dioxide. Dry powder. Foam. Water spray.

Unsuitable extinguishing media

: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: No particular fire or explosion hazard.

Reactivity

: No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions

: Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter

drains or water courses.

Protection during firefighting

Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear a self contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

Protective equipment

: Where excessive dust may result, use approved respiratory protection equipment.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment

: Where excessive dust may result, use approved respiratory protection equipment.

Emergency procedures

: Ventilate area.

6.2. Environmental precautions

Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

For containment

: Avoid generating dust. Contain and collect as any solid.

Methods for cleaning up

: Minimize generation of dust. On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible products

: Strong acids. Strong oxidizers. Strong bases.

Storage area

: Store in dry, cool, well-ventilated area.

24/06/2015 EN (English) SDS Ref.: LACO1505005 2/1

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACCILI		ple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green	
ACGIH	Not applicable		
OSHA	Not applicable		
barium bis[2-[(2-hydro	oxynaphthyl)azo]naphthalenesuphonate] (1103-	18-4)	
ACGIH	Not applicable		
OSHA	Not applicable		
Iron oxide red (1309-3	7-1)		
ACGIH	ACGIH TWA (mg/m³)	5 mg/m³	
ACGIH	Remark (ACGIH)	Pneumoconiosis	
OSHA	OSHA PEL (TWA) (mg/m³)	10 mg/m³	
Canada (Quebec)	VEMP (mg/m³)	5 mg/m³ (Fer, trioxyde de, fumées et poussières (exprimée en Fe)) 10 mg/m³ (Rouge)	

8.2. Exposure controls

Appropriate engineering controls

: Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Ensure good ventilation of the work station.

Personal protective equipment

: Avoid all unnecessary exposure.

Hand protection

: None under normal use.

Eye protection

ACGIH

OSHA

: No special eye protection equipment recommended under normal conditions of use. In case of

dust production: protective goggles.

Respiratory protection

: In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Not applicable

Not applicable

Physical state

: Solid

Appearance

: A solid crayon-like marker.

Odour

: Variable. : wax like.

Odour threshold

: No data available

pН

Colour

: No data available

Relative evaporation rate (butyl acetate=1)

: No data available

Melting point

No data available

Freezing point

: 60 - 85 °C

r reezing point

: No data available

Boiling point

: No data available

Flash point

: 177 °C

Auto-ignition temperature
Decomposition temperature
Flammability (solid, gas)
Vapour pressure

: No data available: No data available: No data available

Relative vapour density at 20 °C

No data availableNo data available

Relative density Solubility : > 1 Specific Gravity: insoluble in water.

24/06/2015

EN (English)

SDS Ref.: LACO1505005

3/1

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

Log Pow

: < 1

Log Kow

: No data available

Viscosity, kinematic

: No data available

Viscosity, dynamic

: No data available

Explosive properties

: No data available

Oxidising properties

: No data available

Explosive limits

: No data available

9.2, Other information

VOC content

: 0%

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

Hazardous polymerization will not occur.

Conditions to avoid

None known.

incompatible materials 10.5.

Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effect	
Acute toxicity	: Not classified
LUMBER CRAYON 500 : White, Yellow, Re	d, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green
LD50 oral rat	> 5000 mg/kg (yellow)
barium bis[2-[(2-hydroxynaphthyl)azo]nap	hthalenesuphonatel (1103-38-4)
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	4.13 mg/V4h
ATE CLP (vapours)	4.130 mg/l/4h
ATE CLP (dust,mist)	4.130 mg/l/4h
Iron oxide red (1309-37-1)	THE THE SHOP WITH THE THE THE THE THE THE THE THE THE T
LD50 oral rat	> 10000 mg/kg
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-etho (2786-76-7)	oxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)
LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m³ 4 h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified.
Serm cell mutagenicity	: Not classified
arcinogenicity	: Not classified.
Iron oxide red (1309-37-1)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Not listed in carcinogenicity class
eproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated

: Not classified

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

Likely routes of exposure

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

Aspiration hazard

: Not classified

Potential adverse human health effects and symptoms

: Skin and eye contact;Inhalation

SECTION 12: Ecological information

12.1

barium bis[2-[(2-hydroxynapht	hyi)azo]naphthalenesuphonate] (1103-38-4)
LC50 fish 1	50 mg/l 48 h
EC50 Daphnia 1	> 3.8 mg/l 48 h
Iron oxide red (1309-37-1)	
EC50 Daphnia 1	> 100 mg/l
4-[[4-(aminocarbonyl)phenyl]a: (2786-76-7)	zo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h

12.2. Persistence and degradability

barium bis[2-[(2-hydroxynaphthyl)aze	o]naphthalenesuphonate] (1103-38-4)	
Persistence and degradability Not readily biodegradable. Product persists.		
4-[[4-(aminocarbonyl)phenyl]azo]-N-((2786-76-7)	2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol ≺1%)	
Persistence and degradability	lity Not readily biodegradable,	
Biodegradation	0 % 28 d	

12.3. Bioaccumulative potential

Log Pow	hite, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green
barium bis[2-[(2-hydroxyna	phthyl)azo]naphthalenesuphonate] (1103-38-4)
BCF fish 1	1.7 - 1.8 mg/l .3 mg/l conc. in envir/dose
Log Pow	-0.67 - 1.07
4-[[4-(aminocarbonyl)pheny (2786-76-7)	/I]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol ≤1%)
BCF fish 1	53 Vkg
Log Pow	1.28

12.4. Mobility in soil

No additional information available

Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment methods

: Dispose in a safe manner in accordance with local/national regulations.

Sewage disposal recommendations

: Do not dispose of waste into sewer.

SECTION 14: Transport information

In accordance with DOT and TDG

Not considered a dangerous good for transport regulations

Proper Shipping Name (ADR)

: Not applicable

1.28

Transport by sea

No additional information available

Air transport

No additional information available

24/06/2015 EN (English) SDS Ref.: LACO1505005 5/1

LUMBER CRAYON 500: White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

SECTION 15: Regulatory information

15.1. US Federal regulations

barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Iron oxide red (1309-37-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

barium bis[2-[(2-hydroxynaphthyi)azo]naphthalenesuphonate] (1103-38-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Iron oxide red (1309-37-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

barium bis[2-[(2-hydroxynaphthyl)azo]naphthalenesuphonate] (1103-38-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Iron oxide red (1309-37-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

LUMBER CRAYON 500 : White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

Iron oxide red (1309-37-1)

U.S. - Minnesota - Hazardous Substance List

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes

Data sources

: Original Document.

: ACGIH (American Conference of Government Industrial Hygienists).

European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database.

Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Ctothing", Fifth Edition.

National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.

OSHA 29CFR 1910.1200 Hazard Communication Standard.

TSCA Chemical Substance Inventory. Accessed at

http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html.

24/06/2015

LUMBER CRAYON 500: White, Yellow, Red, Green, Blue, Orange, Purple, Fluorescent Orange, Fluorescent Yellow, Fluorescent Green

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

Abbreviations and acronyms

: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number.

CLP: Classification, Labelling, Packaging.

EC50: Environmental Concentration associated with a response by 50% of the test population.

GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).

LD50: Lethal Dose for 50% of the test population.
OSHA: Occupational Safety & Health Administration.

PBT: Persistent, Bioaccumulative, Toxic.

TWA: Time Weight Average.

TSCA: Toxic Substances Control Act.

Other information

: None.

NFPA health hazard

: 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.


NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions,

and not reactive with water.



Full text of H-statements:

Acute Tox, 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Skin Sens. 1	Sensitisation — Skin, category 1
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS Prepared by: The Redstone Group, LLC

6077 Frantz Rd. Suite 206 Dublin, OH USA 43016 T 614-923-7472 www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

24/06/2015 EN (English) SDS Ref.: LACO1505005 7/1