

SAFETY DATA SHEET

BATTERY ELECTROLYTE / BATTERY ACID

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name

Battery Electrolyte/Battery Acid (diluted sulfuric acid)

Other means of identification

UN number

UN2796

Recommended use of the chemical and restrictions on use

Recommended Use:

Used to activate dry batteries.

Uses advised against:

Any other not listed above.

Details of the supplier of the safety data sheet

Supplier Address:

Interstate Batteries, Inc.

12770 Merit Drive

Dallas, Texas 75251

United States

www.interstatebatteries.com

Emergency telephone number

Information Phone Number

(972)991-1444, Ext. 6672 and Ext. 6663

24 Hour Emergency Phone Number In the U.S.: (800) 255-3924, Chemtel

2. HAZARDS IDENTIFICATION

Classification

Health Hazards

Skin corrosion/irritation	Category 1A
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A

Physical hazards

Not classified

OSHA Regulatory Status

Under United States Regulations (29 CFR 1900.1200 – Hazard Communication standard), this product is considered hazardous. In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS). According to the Globally Harmonized Standard for Classification and Labeling (GHS) this product is considered hazardous

Label elements

Emergency Overview

Danger

Hazard statements

Causes severe skin burns and eye damage May cause cancer



Appearance Clear liquid.

Physical state Liquid

Odor Pungent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Precautionary Statements - Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

May be harmful if swallowed.

Unknown Acute Toxicity

65% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Under United States Regulations (29 CFR 1900.1200 – Hazard Communication standard), this product is considered hazardous. In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS). According to the Globally Harmonized Standard for Classification and Labeling (GHS) this product is considered hazardous.

Synonyms

Not available.

Chemical Name	CAS No.	Weight-%
Sulfuric Acid	7664-93-9	30-40

4. FIRST AID MEASURES

First aid measures

Eye contact In case of eye contact, immediately flush eyes with fresh water for at least 15 minutes while

holding the eyelids open. Remove contact lenses if worn. Get medical attention if irritation

persists.

Skin Contact For minor skin contact, avoid spreading material on unaffected skin. In case of contact with

substance, immediately flush skin with running water for at least 20 minutes. Remove and

isolate contaminated clothing and shoes.

In case of inhalation, remove to fresh air. If not breathing, provide artificial respiration. If

breathing is difficult, administer oxygen. Seek medical attention immediately.

In case of accidental ingestion, wash out mouth with copious amounts of water. Seek

medical attention immediately. Do not induce vomiting unless directed by medical

personnel. Never give anything by mouth to an unconscious person.

Self-protection of the first aider Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give

artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Most important symptoms and effects, both acute and delayed

Symptoms Not available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire

Dry chemical, CO₂, or water spray.

Large Fire

Dry chemical or CO₂, alcohol - resistant foam or water spray.

Unsuitable extinguishing media Any not listed above.

Specific hazards arising from the chemical

Hazardous combustion products Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive fumes.

Explosion data

Sensitivity to Mechanical Impact None known.
Sensitivity to Static Discharge None known.

Protective equipment and precautions for firefighters

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible. Wear chemical protective clothing that is specifically recommended by the manufacturer, It may provide little or no thermal protection. As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep out of low areas. Keep unauthorized personnel away. Stay upwind.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ventilate enclosed areas. Do not touch damaged containers or spilled material unless

wearing appropriate protective clothing.

Other Information Non-emergency personnel should utilize chemical gloves.

For emergency responders ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) as

an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low

areas. Do not get water inside container.

Personal protective equipment: Wear chemical gloves, goggles, acid resistant clothing and

boots, respirator if insufficient ventilation.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for

additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Absorb with earth sand or other non-combustible

material. Do not allow discharge of un-neutralized acid to sewer. Cautiously neutralize

spilled liquid.

Methods for cleaning up Dispose of in accordance with local, State, and national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling Advice on safe handling

Handle and open container with care. Avoid contact with skin and eyes. Use only with adequate ventilation. Use caution when combining with water; DO NOT add water to corrosive liquid, ALWAYS add corrosive liquid to water while stirring to prevent release of

heat, steam and fumes.

Do not get in eyes or on skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Eyewash stations and safety showers should be provided with unlimited water supply. Handle in accordance with good

industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from incompatible materials. Store locked up. Keep container/package tightly

closed in a cool, well-ventilated place. Ventilate enclosed areas.

Storage class:

Class 8B: Non-flammable corrosive materials.

Incompatible materials Reacts violently with strong reducing agents, metals, sulfur trioxide, strong oxidizers and

water. Contact with metals may product toxic sulfur dioxide fumes and may release

flammable hydrogen gas.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Sulfuric Acid	TWA: 0.2 mg/m³ thoracic fraction	TWA: 1 mg/m ³	IDLH: 15 mg/m ³
7664-93-9		_	TWA: 1 mg/m ³

Appropriate engineering controls

Engineering Controls

The health hazard risks of handling this material are dependent on factors, such as physical form and quantity. Site-specific risk assessments should be conducted to determine the appropriate exposure control measures. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels as low as reasonably achievable.

Individual protection measures, such as personal protective equipment

Eye/face protection

In laboratory, medical or industrial settings, safety glasses with side shields are recommended. The use of goggles or full face protection may be required depending on the industrial exposure setting. Contact a health and safety professional for specific information.

Skin and body protection

Wear protective gloves with elbow length gauntlet. Wear synthetic apron. Under severe exposure or emergency conditions, wear acid-resistant clothing and boots.

Respiratory protection

None required under normal conditions of use. Follow the OSHA respirator regulations found in 29 CFR1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

General Hygiene Considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state

Liquid

Appearance

Color

Clear liquid. Clear

Odor

Odor threshold

Pungent No Data

Property **Values** No Data No Data

Melting point/freezing point Boiling point / boiling range

95 °C - 95.5556 °C No Data

Flash point **Evaporation rate**

1 n-butyl, Acetate=1

Flammability (solid, gas) Flammability Limit in Air

No Data

Upper flammability limit: Lower flammability limit:

No Data No Data Vapor pressure Vapor density

10 mmHg

Specific Gravity Water solubility

1.215-1.35 100%

Solubility in other solvents Partition coefficient

No Data No Data

Autoignition temperature **Decomposition temperature** Kinematic viscosity Dynamic viscosity

No Data No Data No Data

Explosive properties Oxidizing properties No Data No Data No Data

Other Information

Softening point Molecular weight

No Data No Data

VOC Content (%)

Not available.

Density

10.1392-11.2658 lbs/gal

Bulk density

No Data

10. STABILITY AND REACTIVITY

Reactivity

Not reactive.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Contact with organic materials, combustibles, strong reducing agents, metals, strong oxidizers, water.

Incompatible materials

Reacts violently with strong reducing agents, metals, sulfur trioxide, strong oxidizers and water. Contact with metals may product toxic sulfur dioxide fumes and may release flammable hydrogen gas.

Hazardous Decomposition Products

Sulfur trioxide, carbon monoxide, sulfuric acid fumes, and sulfur dioxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

(Acute): May cause corrosive burns - irreversible damage.

(Chronic): Repeated or prolonged exposure to corrosive fumes may cause bronchial

irritation with chronic cough.

Eye contact

(Acute): Causes serious eye damage.

(Chronic): Repeated or prolonged exposure to corrosive materials or fumes may cause

conjunctivitis.

Skin Contact

(Acute): Causes severe skin burns and eye damage.

(Chronic): Repeated or prolonged exposure to corrosive materials will cause dermatitis.

Ingestion

(Acute): May cause irreversible damage to mucous membranes.

(Chronic): Repeated or prolonged exposure to corrosive materials or fumes may cause

gastrointestinal disturbances.

Acute Effects

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Sulfuric Acid	= 2140 mg/kg (Rat)	•	= 510 mg/m³ (Rat) 2 h
7664-93-9			

Information on toxicological effects

Symptoms

Not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Not available.

Serious eye damage/eye irritation

Effective dose; 5mg Rabbit, 30 second rinse. Severe eye irritation.

Irritation Corrosivity

Severe burns. Not available.

Sensitization Germ cell mutagenicity Not available. Not available.

Carcinogenicity

The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mist containing sulfuric acid" as a Category 1 carcinogen, a substance that is carcinogenic to humans. This classification does not apply to liquid forms of sulfuric acid or sulfuric acid solutions contained within a battery. Batteries subjected to abusive charging at excessively high currents for prolonged periods without vent caps in place may create a surrounding atmosphere of the offensive strong inorganic acid mist containing sulfuric acid.

Chemical Name	ACGIH	IARC	NTP	OSHA
Sulfuric Acid	A2	Group 1	-	×
7664-93-9				

Reproductive toxicity

Not available.

Developmental Toxicity Teratogenicity

Not available. Not available.

STOT - single exposure

Not classified. Not classified.

STOT - repeated exposure Chronic toxicity

Not available.

Subchronic toxicity

Not available.

Target Organ Effects Aspiration hazard

Not available. Not available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity

65% of the mixture consists of ingredient(s) of unknown toxicity

12. ECOLOGICAL INFORMATION

Ecotoxicity

65% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Sulfuric Acid		500: 96 h Brachydanio rerio		29: 24 h Daphnia magna
7664-93-9		mg/L LC50 static		mg/L EC50

Persistence and degradability

Not available.

Bioaccumulation

Not available.

Mobility

Not available.

Other adverse effects

Not available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Not available.

California Hazardous Waste Codes Not available

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
Sulfuric Acid	Toxic	
7664-93-9	Corrosive	

14. TRANSPORT INFORMATION

DOT

UN/ID No.

UN2796

Proper shipping name

Battery fluid, acid

Hazard Class

8

Subsidiary class

8

Packing Group

11

Special Provisions

A3, A7, B2, B15, IB2, N6, N34, T8, TP2, 154

Passenger aircraft/rail: 1.00 L Cargo aircraft/rail: 30.00 L

TDG

UN/ID No.

UN2796

Proper shipping name

Battery fluid, acid

Hazard Class

8

Subsidiary class

8 11

Packing Group Special Provisions

Explosive Limit and Limited Quantity Index: 1.00

Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index: 1.00

<u>MEX</u>

Not regulated

ICAO (air)

UN/ID No.

UN2796

Proper shipping name

Battery fluid, acid

Hazard Class

8

Packing Group

11

Special Provisions

IATA

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class 8 **Packing Group** П **Special Provisions**

<u>IMDG</u>

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class Packing Group Ш **Special Provisions** Marine pollutant No

RID

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class Packing Group II Classification code C1 **Special Provisions** Labels 8

ADR

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class Packing Group 11 Classification code C1 **Special Provisions** Labels 8

<u>ADN</u>

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Complies **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

<u>Legend:</u>
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Sulfuric Acid - 7664-93-9	7664-93-9	35	1.0

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sulfuric Acid 7664-93-9	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sulfuric Acid	1000 lb	1000 lb	RQ 1000 lb final RQ
7664-93-9			RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations

The production of the producti				
	Chemical Name	New Jersey	Massachusetts	Pennsylvania
	Sulfuric Acid	X	X	X
	7664-93-9			i

U.S. EPA Label Information

EPA Pesticide Registration Number Not available.

16. OTHER INFORMATION

Prepared By Issue Date Revision Date

IES Engineers 13-Feb-2014 1-Dec-2014

Revision Note

Not available.

Disclaimer

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Interstate Batteries, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Interstate Batteries, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

End of Safety Data Sheet